



LEAK & GAS DETECTORS

Leak Detectors

- The UT-300 transmits an ultrasonic signal for non pressurized applications
- Tests the "air-tightness" of weather seals, tanks, ovens, refrigerators, etc.
- Locating leaks in duct work
- Finds the ends of buried PVC pipes
- Detects any pressurized gas leak regardless of type CFC's, HFC's, Nitrogen, etc. (unaffected by contaminants)
- **HN256** comes with a detector and a transmitter



HN256



| Model No. | Mfg. No. | Description | Price /Each |
|-----------|-----------|--------------------------|-------------|
| HN256 | TMULD-300 | Leak Detector Kit | |
| HK991 | ULD-300 | Ultrasonic Leak Detector | |
| HN258 | UT-300 | Ultrasonic Transmitter | |

BatCam 2.0 Ultrasonic & Sound Detection Cameras

- Measurement of 96 000 samples per second
- Includes distance range sensor, adjustable lighting, real-time visualization of sound, desired frequency range filtering, image averaging function and video and image storage
- Sensor (Microphone): 112 Channel Digital MEMS
- Effective Frequency Range: 2 k to 48 kHz
- Microphone Sensitivity: -41 dBFS
- Signal-To-Noise Ratio: 66 dB(A)
- Camera Frame Speed: 25 FPS
- Detection Distance: More than 0.98' (0.3 m)
- Display Type: 5" Mono-Colour LCD
- Operating Temperature: -4 to 122°F (-20 to 50°C)



| Model No. | Mfg. No. | Description | Price /Each |
|-----------|----------|-------------------------------------|-------------|
| IC545 | BATCAM | Ultrasonic & Sound Detection Camera | |

Ultrasonic Leak Detectors

- Locates leaks generated by pressure, vacuum, water, gas or air
- Visible (LED) and Audible (ticking) alarms assist in pinpointing leaks
- Earphone jack for loud environments (earphones included)
- User adjustable sensitivity wheel
- Ultrasonic Transmitter generates a 40 kHz signal
- Includes a reference table displaying pH vs. temperature
- Includes: Leak Detector, transmitter, headphones, carrying case and batteries
- Alert Type: Light & Sound
- Earphone Jack: Yes (Earphones included)
- Power Supply: 2 x 9V Batteries
- Operating Temperature: 32 to 104°F (0 to 40°C)



| Model No. | Mfg. No. | Description | Price /Each |
|-----------|----------|--------------------------|-------------|
| IB944 | R9100 | Ultrasonic Leak Detector | |

Tru Pointe® Ultra Ultrasonic Leak Detectors

- Detects leaks of any gas type, but can also be used for thermal expansion valves, steam traps, bearings and more
- Visual and audible indicators include an LED scale and a headphone jack
- Includes: Instrument, Probe wrench, Touch probe, 6" wave guide, Folding headset, 9 V battery, User manual, Hard carrying case
- Gases Detected: All Gases
- Sensitivity: Continually Variable Slide Adjustment
- Response Time: Instantaneous
- Manufacturer's Warranty: 1 Year

IC426



| Model No. | Mfg. No. | Description | Price /Each |
|-----------|-----------|---|-------------|
| IC426 | 0028-8010 | Ultrasonic Leak Detector with Sound Blaster | |
| IC424 | 0028-8000 | Ultrasonic Leak Detector | |

Refrigerant Leak Detectors

- This refrigerant leak detector is capable of pinpointing small leaks quickly and accurately with audible and visual indicators
- Features a tricolour LED bar indicator with high and low sensitivity functions
- Features a 15" (390 mm) gooseneck for hard to reach areas
- Designed for one-handed operation
- Features high and low sensitivity settings, a low battery indicator, and auto shut off
- User replaceable sensor
- Requires no field calibration
- Measures CFC, HCFC and HFC refrigerants
- Quick response and high accuracy detects small leaks
- Uses (4) AA batteries
- Detected Gases: CFC's (R11, R12, R13), HCFC's (R22, R502, R500), HFC's (R134a, R123, R125, R23, R404A, R407C, R410A and other halogen based compounds)
- Includes: (1) Refrigerant leak detector, (1) Reference leak source, (4) Batteries, (1) Hard carrying case



| Model No. | Mfg. No. | Description | Price /Each |
|-----------|------------|---|-------------|
| IA450 | C-380 | Refrigerant Leak Detector | |
| NJW086 | C-380-NIST | Refrigerant Leak Detector w/ISO Certificate | |
| IB742 | R8888 | Carrying Case | |

Informant®2 Dual Purpose Leak Detectors

- Detects refrigerants and combustible gases with respective sensor installed, changing sensors takes only seconds
- Sensor located in the probe tip for ultimate sensitivity, fast response and easy changing
- Visual and audible indicators include dual LED scales, flashing LED in probe tip and a speaker with mute option
- CE approved, SAE J1627 (refrigerant sensor only), UL 913 Class 1, Division 1, Group D (combustible sensor only)
- Includes: (1) Set of refrigerant and combustible gas sensors, (1) Set of colour-coded probe tips, (1) Rubber boot, (1) Instruction manual, (4) AA batteries, (5) Filters, (1) Hard carrying case
- Refrigerants Detected: All CFC, HFC and HCFC Refrigerants
- Combustible Gases Detected: All Hydrocarbons/Combustible Gases



| Model No. | Mfg. No. | Description | Price /Each |
|-----------|-----------|----------------------------|-------------|
| IC417 | 0019-8038 | Dual Purpose Leak Detector | |