



### 3 1/2" Non-Vacuum Dynorbital-Spirit™ Random Orbital Sanders

- Replaceable drop-in motor
- Palm-style grip; colour coded composite lever (identifies orbit size)
- Low sound levels
- One-piece speed control dial
- Custom engineered composite cylinder; double row balancer bearing keeps out contaminants
- Includes low profile, premium urethane, weight-mated, non-vac pad
- Can be converted easily to self-generated or central vac model for hook-up to dust collection system



<b>Model No.</b>	<b>TGY858</b>
<b>Mfg. No.</b>	59015
<b>Abrasive Information:</b>	3 1/2" (89 mm) dia. discs
<b>Pad Information:</b>	3 1/2" (89 mm) dia. pad
<b>Air Flow Rate @ 90 PSI:</b>	16 SCFM
<b>Sound Level:</b>	73 dB (A)
<b>Horsepower:</b>	0.25 HP
<b>Free Speed:</b>	12 000 RPM
<b>Air Pressure:</b>	90 PSI
<b>Air Inlet Thread:</b>	1/4 NPT
<b>Hose Size (I.D.):</b>	1/4" (6 mm)
<b>Orbit Diameter:</b>	3/16" (4.8 mm)
<b>Tool Spindle Thread:</b>	5/16"- 24 female
<b>Length:</b>	6" (152 mm)
<b>Height:</b>	3 1/2" (89 mm)
<b>Weight:</b>	1.4 lbs. (0.64 kg)
<b>Price/Each:</b>	\$



### 3 1/2" Non-Vacuum Dynorbital® Supreme Random Orbital Sanders

- Includes low profile, premium urethane, weight-mated, non-vac pad for use with PSA discs
- Can be converted easily to self-generated vac model for hook-up to dust collection system
- Random circular & elliptical motion produces superior finishes



<b>Model No.</b>	<b>TGY810</b>
<b>Mfg. No.</b>	56800
<b>Abrasive Information:</b>	3 1/2" (89 mm) dia. discs
<b>Pad Information:</b>	3 1/2" (89 mm) dia.
<b>Length:</b>	6" 152 mm
<b>Height:</b>	3 3/4" (95 mm)
<b>Weight:</b>	2.1 lbs. (0.95 kg)
<b>Air Flow Rate @ 90 PSI:</b>	18 SCFM
<b>Sound Level:</b>	76 dB(A)
<b>Horsepower:</b>	0.24 HP
<b>Free Speed:</b>	12 000 RPM
<b>Air Pressure:</b>	90 PSI
<b>Air Inlet Thread:</b>	1/4 NPT
<b>Hose Size (I.D.):</b>	1/4" (6 mm)
<b>Orbit Diameter:</b>	3/16" (4.8 mm)
<b>Tool Spindle Thread:</b>	5/16"- 24 female
<b>Price/ Each:</b>	\$



### 5" & 6" Non-Vacuum Dynorbital® Supreme Random Orbital Sanders

- Can be converted easily to self-generated vac model for hook-up to dust collection system
- Random circular & elliptical motion produces superior finishes
- Includes low profile, premium urethane, weight-mated, non-vac pad



Model No.	TGY813	TGY816
<b>Mfg. No.</b>	56815	56826
<b>Abrasive Information:</b>	5" (127 mm) dia. discs	6" (152 mm) dia. discs
<b>Pad Information:</b>	5" (127 mm) dia.	6" (152 mm) dia.
<b>Air Flow Rate @ 90 PSI:</b>	18 SCFM	18 SCFM
<b>Sound Level:</b>	79 dB (A)	79 dB (A)
<b>Horsepower:</b>	0.28 HP	0.24 HP
<b>Free Speed:</b>	12 000 RPM	12 000 RPM
<b>Air Pressure:</b>	90 PSI	90 PSI
<b>Air Inlet Thread:</b>	1/4 NPT	1/4 NPT
<b>Hose Size (I.D.):</b>	1/4" (6 mm)	1/4" (6 mm)
<b>Orbit Diameter:</b>	3/16" (4.8 mm)	3/16" (4.8 mm)
<b>Tool Spindle Thread:</b>	5/16"- 24 female	5/16"- 24 female
<b>Length:</b>	6 1/2" (165 mm)	7" (178 mm)
<b>Height:</b>	3 5/8" (92 mm)	3 1/2" (89 mm)
<b>Weight:</b>	2.1 lbs. (0.95 kg)	2.2 lbs. (1 kg)
<b>Price/Each</b>	\$	\$



### Air Line Connectors

- Swivels 360° at two pivot points allowing the air hose to drop directly to the floor while providing superb tool handling



THZ359



THZ360



THZ361



#### COMPOSITE DYNASWIVEL® AIR LINE CONNECTORS

<b>Model No.</b>	<b>THZ359</b>
<b>Mfg. No.</b>	94300
<b>Thread Size:</b>	1/4" NPT
<b>Weight:</b>	2.15 oz. (0.06 kg)
<b>Air Flow Range:</b>	Up to 33 SCFM
<b>Maximum Air Pressure:</b>	150 PSI
<b>Price/Each:</b>	\$

#### 1/4" NPT HEAVY-DUTY DYNASWIVEL® AIR LINE CONNECTORS

<b>Model No.</b>	<b>THZ361</b>
<b>Mfg. No.</b>	95460
<b>Air Inlet Thread Size:</b>	1/4" NPT
<b>Air Flow Range:</b>	Up to 25 SCFM
<b>Maximum Air Pressure:</b>	150 PSI
<b>Weight:</b>	0.20 lbs. (0.09 kg)
<b>Price/ Each:</b>	\$

#### COMPOSITE FLOW CONTROL DYNASWIVEL® AIR LINE CONNECTORS

<b>Model No.</b>	<b>THZ360</b>
<b>Mfg. No.</b>	94407
<b>Thread Size:</b>	1/4" NPT
<b>Air Flow Range:</b>	Up to 46 SCFM
<b>Maximum Air Pressure:</b>	150 PSI
<b>Weight:</b>	2.4 oz. (0.08 kg)
<b>Price/Each:</b>	\$