



Gearhead Milling Drilling Machines

- Spindle is equipped with four heavy-duty tapered roller bearings
- Forward and reverse switch
- Head tilts 90° to the left and 30° to the right
- Includes: 1/2" chuck with key, 3 1/2" angle vise and safety guard



Model No. BV698
Mfg. No. KC-40HC
Drilling capacity: 1 1/4"
Diameter of column: 4 1/2"
Speeds: 6 (60-1500 RPM)
Table size: 23" x 7 1/2"
Size of T-slot on table: 1/2"
Motor: 1.5 HP, 11 A, 1 phase, 60 Hz
Voltage: 220 V
Dimensions: 38" L x 37" W x 78" H
Approx. shipping weight: 630 lbs.
Price/Each \$

Milling Drilling Machines

- Spindle is equipped with four heavy-duty tapered roller bearings
- Table control hand wheels have large micrometer dials graduated in 0.001"
- Head swivels 360° and is easily raised and lowered
- Includes: 3" face cutter, 1/2" chuck with key, 3 1/2" angle vise and safety guard



Model No. TS218
Mfg. No. PDM-30
Drilling capacity: 1 1/4"
Diameter of column: 4 3/4"
Speeds: 12 (150-2500 RPM)
Working area of table: 8 1/4" x 28 3/4"
Size of T-slot on table: 5/8"
Motor: 22 A @ 110 V, 11 A @ 220 V, 1 phase, 60 Hz
Voltage: 110 V
Pre-wired at: 110 V
Dimensions: 43" L x 39" W x 42" H
Approx. shipping weight: 600 lbs.
Price/Each \$



ACCESSORY

Model No. TS221
Mfg. No. SS-45
Description Optional stand for TS218
Dimensions 31" x 21 1/2" x 28 1/4"
Price/Each \$

Milling Drilling Machines with Digital Readouts

- Powerful 1 HP single phase DC motor
- Spindle depth digital readout and control panel with metric and imperial readings
- Spindle RPM digital readout
- Head tilts 90° to the right or left
- Spindle depth fine feed knob
- Forward/reverse switch and variable speed selector dials
- Comes with 1/2" chuck, chuck key, R8 chuck arbor, safety guard, two T-bolts, oil bottle, adjustment wrenches, hex keys and tool box



Model No. TMA019
Mfg. No. KC-20VS
Drilling capacity in cast-iron: 3/4"
Drilling capacity in steel: 5/8"
Max. distance spindle nose to table: 13"
Swing: 13"
Spindle taper: R8
Spindle stroke: 2"
Speeds: 2 (50-1125/100-2250 RPM)
Face mill capacity: 2 1/2"
End mill capacity: 3/4"
Max. longitudinal travel: 18 7/8"
Cross travel: 6 7/8"
Working area of the table: 7 1/16" x 27 1/2"
Size of T-slot on table: 1/2"
Motor: 3.2 A, 5600 RPM
Voltage: 110 V, 1 phase, 60 Hz
Dimensions: 35 1/2" x 22" x 36 1/4"
Weight: 265 lbs.
Price/Each \$

OPTIONAL STAND

Model No. TMA020
Price/Each \$

Swivel Base Milling Vises



Model No.	WJ046	WJ047
Mfg. No.	KMV-4M	KMV-6M
Jaw width:	4"	6"
Jaw opening:	4"	6"
Weight:	40 lbs.	80 lbs.
Price/Each	\$	\$

18-Pc. Collet Sets



Model No. BV706
Mfg. No. KCS-R8-15
Straight shank taper: R8
Draw bar: 7/16" NF20
Collet sizes: 1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1"
Price/Each \$

Compound Slide Tables



Model No. WJ045
Mfg. No. KCT-618
Table size: 6" x 18 1/2"
Longitudinal travel: 12"
Transversal travel: 7"
Size of T-slot on table: 1/2"
Weight: 50 lbs.
Price/Each \$



52-Pc. Clamping Kits

Model No. BC884
Mfg. No. KCL-5212
Fits 1/2" table slots
Price/Each \$

Model No. TEX160
Mfg. No. KCL-52
Fits 5/8" table slots
Price/Each \$

