

#### **6" Industrial Jointers**

- · Parallelogram table adjustment system
- 3-knife cutterhead: allows rapid cutting while producing a superior finish
- Spiral cutterhead: makes 50% less noise than a conventional cutterhead
- · Precision ground cast-iron tables
- One piece welded cabinet stand has built-in 4" dust chute for dust collector hook-up
- Lever actuated infeed table with lock handle, for quick easy height adjustment
- Graduated scale located on fence
- · Magnetic safety switch
- Includes 2 safety push locks



Capacity:
Cutterhead speed:
Dia. of cutterhead:
Rabbeting capacity:
Table:
Fence size:
Motor:
Voltage:
Dimensions:
Weight:
-knife cutterhead

3-knife cutterhead Model No. WK940 Mfg. No. KC-70FX Price/Each \$ 6" 5500 RPM 3 3/8" 1/2" x 6" 6" x 55 1/2" 36" x 5" 2 HP, 15 A, 1 phase, 60 Hz 110 V 55 1/2" L x 24" W x 32" W

328 lbs.

Spiral cutterhead
Model No. TMA042
Mfg. No. KC-75FX
Price/Each \$

## 8" Industrial Jointers

- · Parallelogram table adjustment system
- 3-knife cutterhead: allows rapid cutting while producing a superior finish
- Spiral cutterhead: makes 50% less noise than a conventional cutterhead
- · Precision ground cast-iron tables
- One piece welded cabinet stand has built-in 4" dust chute for dust collector hook-up
- Lever actuated infeed table with lock handle, for quick easy height adjustment
- Graduated scale located on fence
- · Magnetic safety switch
- · Includes 2 safety push locks





Capacity:
Cutterhead speed:
Dia. of cutterhead:
Rabbeting capacity:
Table:
Fence size:
Motor:
Voltage:
Dimensions:
Weight:

3-knife cutterhead Model No. WK942 Mfg. No. KC-80FX Price/Each \$ 8" 5500 RPM 3 3/8" 5/8" x 8 1/16" 8" x 76 1/2" 36" x 5" 2 HP, 9 A, 1 phase, 60 Hz 220 V 76 1/2" L x 26" W x 32" H 394 lbs.

Spiral cutterhead Model No. TMA043 Mfg. No. KC-85FX Price/Each \$

**TMA044** 

KC-382CFX

15'

6"

### 15" Industrial Planers

- Cutterhead raises and lowers on four precision ground columns for extra stability
- Anti-kickback fingers in front of the infeed roller to prevent wood kickback
- Magnetic safety switch
- · Extension tables provide support for longer material
- · Mobile base system built into the cabinet
- Includes cabinet with stand, planning knives, knife setting gauge and 4" dust collector outlet



Model No.
Mfg. No.
Max. planing width:
Max. planing thickness:
Max. depth of cut:
Cutterhead speed:
Dia. of cutterhead:
Number of knives:
Feed rate:
Number of cuts/in.
Motor:
Voltage:
Dimensions:
Weight:
Price/Each

1/8"
5000 RPM
3"
3
2 (16-30) FPM
78-42
3 HP, 18 A, 1 phase, 60 Hz
220 V
28 1/2" L x 42" W x 51" H
450 lbs.

#### 15" Planers

- Table raises and lowers on four precision ground columns for extra stability
- Anti-kickback fingers in front of the infeed roller to prevent wood kickback
- Magnetic safety switch
- Stock returns rollers on top of planer for multiple passes
- Extension tables provide support for longer material
- Lever allows you to shift gears for changing feed rates for excellent results in planning hard and soft woods
- Knives rest on adjustable jack screws; lock bar and lock screws keep knives in place
   Includes: Cabinet stand, planning knives.
- Includes: Cabinet stand, planning knives, knife setting gauge and 4" dust collector outlet

Max planning width: 15" Max planning thickness: 6" Max depth of cut: 1/8" Cutter head speed: 5000 RPM Cutter head dia. 2 7/8 Number of knifes: 2 (16/30) FPM Feed rate: Number of cuts / inch: 78/63 Motor: 3 HP, 15 A, 1 phase, 60 Hz

3-knife cutterhead Model No. TJZ786 Mfg No KC-385FX Price/Each \$

Spiral cutterhead Model No. TMA045 Mfg No KC-390FX Price/Each \$

# 20" Industrial Planers

- Solid cast-iron extension tables
- Mobile base system built into cabinet
- 3-knife cutterhead: allows rapid cutting while producing a superior finish

Table raises and lowers on four precision

- Spiral cutterhead: makes 50% less noise than a conventional cutterhead
- ground columns for extra stability

  Anti-kickback fingers in front of the
- infeed roller prevents wood kickback
- Magnetic safety switch
  Includes: knife setting gauge and 5" dust chute

Max. planing width: 20" Max. planing thickness: 8" Max. depth of cut: 3/32" Total surface of work table: 56 1/2" x 20" Cutterhead speed: 5000 RPM Dia. of cutterhead: 3.15 Number of knives: 4 2 (16-20) FPM Feed rate: Number of cuts/in. 104-83 Motor: 3 HP, 18 A, 1 phase, 60 Hz Voltage: 220 V 40" L x 56 1/2" W x 42" H **Dimensions:** 

3-knife cutterhead Model No. TBW141 Mfg. No. KC-520C Price/Each \$

Weight:

Spiral cutterhead Model No. TMA046 Mfg. No. KC-525FX Price/Each \$

830 lbs.





Voltage:

Dimensions: Weight: 220 V

32 1/2" L x 42" W x 45" H

625 lbs.