

LED Small Wall Packs

- · Wall mount luminaire with a classic design
- Best suited for entrances, underpasses or anywhere controlled security lighting is required
- The tough die cast aluminum housing is moisture and dustproof
- High quality, long life LEDs
- 4KVAC surge protection included
- IP68 light engines with screw free structure
- IP67 drivers and waterproof connections
- Colour Temperature: 4000K
- Colour: Bronze



STANPRO

Model No.	Mfg. No.	Voltage	Wattage	Lamp Output	Price /Each
XE769	WPS-LS1-W/40K	120-277 V	39 W	3605 Lumens	
XE771	WPS-LS1-H/40K	347 V	39 W	3624 Lumens	
XE770	WPS-LS2-W/40K	120-277 V	59 W	4720 Lumens	
XE772	WPS-LS2-H/40K	347 V	59 W	4745 Lumens	

LED Mini Wall Packs

- · High performance multi-purpose luminaire
- Effectively diffuses and distributes the highly efficient LED output to maximize spread while minimizing wattage consumption
- Best suited for security lighting over entrances, stairwells and pedestrian areas
- Polycarbonate housing and lens
- Intégrated photocell
- High quality, long life LEDs
- Estimated lifespan of 50,000 hours
- · 4KVAC surge protection included
- Colour Temperature: 5000K
- Colour: Bronze



STANPRO

Model No.	Mfg. No.	Voltage	Wattage	Lamp Output	Price /Each
XE764	WPI-LS1-W/50K/P	120 V	13 W	770 Lumens	

High Bay Fluorescent Luminaires

- Best suited for high-ceiling warehouses as well as areas where uniform and efficient lighting is required
- Housing is made with 22-gauge rolled steel with enamel powder coating applied post-production
- Miro® 4 reflector has a high efficiency rating of 95%
- Comes standard with a set of hooks and can be installed with aircraft cables
- A 6 ft. white power cable is installed on the luminaire
- · Easy ballast access from below
- · Length: 50-1/4"
- Lamp Type: T5HO
- Does not includefluorescent lamps

XE806

Fluorescent Light Fixtures

- Sealed against water and moisture for wet and damp locations
- Uniform gasketing is inserted around the entire housing, ensuring a complete seal
- Polycarbonate housing and lens that are corrosion resistant and will not rot or rust
- Multiple conduit knockouts in housing ends and top
- Reinforced plastic lens latch clips
- UV stabilized, high clarity lens with prismatic cut-off
- Sealed strain relief/cable gland kit included
- 2 lamps
- Length: 50-1/4"
- IP65 rated
- Does not include fluorescent lamps



STANPRO

Model No.	Mfg. No.	Voltage	Wattage	Price /Each
4 LAMPS	5			
XE806 XE808	F1FB-4M4T5H054-W F1FB-4M4T5H054-H	120 - 277 V 347 V	54 W 54 W	
6 LAMPS	5			
XE807 XE809	F1FB-4M6T5H054-W F1FB-4M6T5H054-H	120 - 277 V 347 V	54 W 54 W	

STANPRO

Model No.	Mfg. No.	Voltage	Wattage	Lamp Type	Price /Each
XE810	VT4F2T5H0054-W	120 - 277 V	54 W	T5H0	/ =
XE811	VT4F2T5H0054-H	347 V	54 W	T5H0	
XE812	VT4F2T8032-W	120 - 277 V	32 W	T8	
XE813	VT4F2T8032-H	347 V	32 W	T8	

LED Shop Light

- Great for warehouses, stairways, stores, factories, and garages
- Connect up to 10 LED lights together
- Bulb Type: LED
- Voltage: 120 V
- Wattage: 42W
- · Overall Height: 2.8'
- Overall Width: 6"
- Overall Length: 47.5"
- Lumens: 4500
- Power Cord Length: 5'
- Colour Temperature: 5000K
- Life Expectancy: 25 000 hrs.
- Certificates: ETL/cETL, ES
- Nominal Length: 4'

Model No. XG691 Price/Each \$

