

## **Heavy-Duty 18-Gauge Shear**

- Shear head attachment rotates 360°
- Lightweight cast aluminum gear housing
- · Lock-on button for continuous operation
- · Includes: 5/32" Hex wrench, Shear head assembly

Model No. TDU745 Mfg. No. JS1300 Price/Each \$

### **SPECIFICATIONS**

Voltage: 120 V
Amperage: 5 A
Strokes per minute: 0-2500
Capacity in Steel: 3/80"
Capacity in Stainless Steel: 3/80"



Tnakita

### **16-Gauge Nibblers**

- Die rotates 360°, easy punch and die replacement for less down time
- · Built-in thickness gauge for convenience
- · Lock-on sliding switch for continuous use
- Includes: Wrench, hex wrench, punch and die

Model No. TW024 Mfg. No. JN1601 Price/Each \$

### **SPECIFICATIONS**

Voltage: 120 V
Amperage: 5.0 Amp
Strokes per minute: 2200
Capacity in Steel: 16 gauge
Capacity in Stainless Steel: 18 gauge
Tool Weight: 3.5 lbs.



# Shears - 16 Gauge

- Built-in thickness gauge for operator convenience
- Sliding on/off thumb switch
- 360° rotatable shear head
- Small circumference, ergonomic motor housing for increased comfort, maneuverability and control

Model No. TNB290 Mfg. No. JS1602 Price/Each \$

#### **SPECIFICATIONS**

Steel cutting capacity (mm): 1.6 Stainless Steel

Cutting Capacity (mm): 1.2 Minimum Cutting Radius (mm): 30 Strokes per minute: 4000



## **16-Gauge Nibblers**

- Cuts up to 7 ft. per minute
- Cutter can be set in eight positions
- Paddle switch
- · Includes: Allen wrench and plate wrench

Model No. TF638 Mfg. No. 6890 Price/Each \$

### **SPECIFICATIONS**

Voltage: 120 V
Amperage: 4.0 Amp
Strokes per minute: 1900
Capacity in Steel: 16 gauge
Capacity in Stainless Steel: 4.8 lbs.
Tool Weight: 120 V



## 18-Gauge Shears

- 360° swivel head
- · Trigger speed control
- Ergonomic tactile grip for optimal user comfort
- Includes: Hex wrench

Model No. THZ879 Mfg. No. 6852-20 Price/Each \$

#### **SPECIFICATIONS**

Voltage: 120 V
Amperage: 6.8 Amp
Strokes per minute: 2500
Capacity in Steel: 18 gauge
Capacity in Stainless Steel: 20 gauge
Tool Weight: 4.1 lbs.



# **10-Gauge Nibblers**

- Cuts up to 8.75 ft. per minute
- · Cutter can be set in eight positions
- Toggle switch
- · Includes: Allen wrench and side handle

Model No. TF637 Mfg. No. 6880 Price/Each \$

#### **SPECIFICATIONS**

Voltage: 120 V AC/DC
Amperage: 4.0 Amp
Strokes per minute: 1000
Capacity in Steel: 12 gauge
Tool Weight: 9.3 lbs.



# **16-Gauge Shears**

- · Construction Type: Double insulated
- Includes: (1) Allen wrench, (1) feeler gauge
- Scroll cuts are a snap with the easy to hold back handle design
  Easily adjusted blades make for easy work adjustment
- A handy tool for sheet metal work

Model No. TF629 Mfg. No. 6805 Price/Each \$

### **SPECIFICATIONS**

 Voltage:
 120 V

 Amperage:
 4 Amp

 Strokes per minute:
 4000

 Capacity in Steel:
 3/50"

 Capacity in Stainless Steel:
 1/20"

 Tool Weight:
 6.15 lbs



# 14-Gauge Shears

- Trigger Lock: On/off
- Construction Type: Double insulated
- Includes: (1) Allen wrench, (1) feeler gauge
- Clear unobstructed visibility
- Blade design eliminates jamming
- Cuts close curves either left or right
- Simple, shim-free blade adjustment

 Leaves edges smooth and burr free Model No. TF631 Mfg. No. 6815

Price/Each \$

### **SPECIFICATIONS**

 Voltage:
 120 V

 Amperage:
 5.0 Amp

 Strokes per minute:
 4000

 Capacity in Steel:
 5/64"

 Capacity in Stainless Steel:
 1/16"

 Tool Weight:
 5.0 lbs.



020 @ TENACUIP Limite