



1-5/8" Electromagnetic Drill Kit

- Optimized cutting & drilling speeds
- Magnetic deadlift (1") 1800 lbs. Auto-Stop function
- Carrying Handle
- Auto-stop lift-off detection
- Tool free feed-handle LED light
- Feed handle can be changed from the left or right side of the tool
- Includes: 1-5/8" Electromagnetic Drill, Lubrication Spray Bottle, 1/2" Chuck Adapter, Chuck Key, (2) 1" Retractable Pilot Pins, Safety Strap & Carrying Case

Model No. TYP028
Mfg. No. 4272-21
Price/Each \$

SPECIFICATIONS

Amperage: 13.0
Voltage: 120 V
Drill Capacity: 1-1/2"/1-5/8"
No Load RPM: 730/475
Drill Point Pressure: 600 lbs.
Drill Travel: 5-3/4"
Stoke Length: 5-3/4"
Tool Weight: 30.0 lbs.



1-1/4" Adjustable Position Electromagnetic Drill Presses

- Solid state electronic switching
- Feedback speed control
- Line Lock-Out prevents tool from operating should voltage be restored to an interrupted line

Model No. TF320
Mfg. No. 4208-1
Price/Each \$

SPECIFICATIONS

Amperage: 12.5
Drill Capacity: 1-1/4"
No Load RPM: 500/250
Drill Point Pressure: 1530/1600 lbs.
Drill Travel: 11"
Tool Weight: 72.0 lbs.



Nova Voyager DVR Drill Press

- Powerful direct-drive, high-torque motor with no pulleys or belts to cause vibration
- Digital Variable Reluctance (DVR) direct-drive technology with Adaptive Control Software, which works for you to produce optimum results in wood, metal, plastic and glass
- Constant torque-under-load, depth and vibration sensors and emergency stop
- Slow-start pilot hole, tapping assist with chip breaking cycle and self-start functions
- Intelligent speed selection and dial knob for precise speed adjustments
- Electronic braking and forward/reverse



Model No. TTY149
Mfg. No. 58006
Chuck Size: 5/8"
No Load Speed: 3000 RPM
Table Size: 16-1/2" W x 16-1/2" L x 1" H
Motor: 1.75 HP, 15 A
Voltage: 120 V, 60 Hz, 1 phase
Dimensions: 17-1/2" W x 22-1/4" L x 70-5/8" H
Price/Each \$

8" Drill Presses

- Spindle is supported by high quality ball bearings
- Switch located at the front of the machine for easy access
- Positive depth stop for quick and easy adjustment
- 45° tilting table for angular drilling
- Includes: 1/2" drill chuck and key



Model No. TM197
Mfg. No. KC-108N
Chuck Size: 1/2"
Speeds: 5 (620-3100 RPM)
Table Size: 6-1/2" x 6-1/2"
Spindle Taper: #33 JT
Motor: 2.5 A, 1 phase, 60 Hz
Voltage: 110 V
Dimensions: 6-3/4" x 16-1/2" x 23"
Weight: 38 lbs.
Price/Each \$

10" Drill Presses w/Laser

- Dual intersecting adjustable laser guides
- Spindle is supported by high quality ball bearings
- Switch located at the front of the machine for easy access
- Positive depth stop for quick and easy adjustment
- 45° tilting table for angular drilling
- Includes: 1/2" drill chuck and key



Model No. TBW135
Mfg. No. KC-110N
Chuck size: 1/2"
Speeds: 5 (570-3050 RPM)
Table size: 7-3/4" x 7-3/4"
Spindle Taper: #33 Jacobs
Motor: 3.2 A, 1 phase, 60 Hz
Voltage: 110 V
Dimensions: 11" L x 18-1/2" W x 29" H
Weight: 70 lbs.
Price/Each \$