



17" Floor Drill Presses

- Spindle is supported by high quality ball bearings
- Cast-iron pulleys reduces vibrations
- Comes with non-slip rubber feed handles
- Tilting table for angular drilling
- Light fixture incorporated into the head casting illuminates the work table (light bulb not included)
- Includes: 5/8" drill chuck and key



TM213



TMA036

w/o Safety Guard

Model No. TM213
Mfg. No. KC-118FC
Price/Each \$

w/Safety Guard

Model No. TMA036
Mfg. No. KM-118FC-(LS)
Price/Each \$

Chuck size: 5/8"
Speeds: 16 (240-3400 RPM)
Table size: 13-3/4"
Spindle Taper: #2 Morse
Motor: 12 A @ 110 V, 6 A @ 220 V
 1 HP, 1 phase, 60 Hz
 110 V/220 V
Voltage:
Dimensions: 13-3/4" L x 25" W x 64" H
Weight: 185 lbs.

22" Floor Drill Presses

- Spindle is supported by high quality ball bearings
- Cast-iron pulleys reduce vibrations
- Tilting table for angular drilling
- Light fixture incorporated into the head casting illuminates the work table (light bulb not included)
- Comes with non-slip rubber feed handles



TM214



TMA037

w/o Safety Guard

Model No. TM214
Mfg. No. KC-122FC
Price/Each \$

w/Safety Guard

Model No. TMA037
Mfg. No. KM-122FC-(LS)
Price/Each \$

Chuck size: 3/4"
Speeds: 12 (150-4200 RPM)
Table size: 18-3/4" x 16-1/4"
Spindle Taper: #4 Morse
Motor: 1 HP, 1 phase, 60 Hz
 12.5 A @ 110 V, 6.25 A @ 220 V
 110/220 V
Voltage:
Dimensions: 18-3/4" L x 33" W x 69" H
Weight: 360 lbs.

21" Gearhead Drilling Machines

- 1.5 HP
- Spindle is equipped with four heavy-duty tapered roller bearings
- Forward and reverse switch
- Head tilts 90° to the left and 30° to the right
- Includes: 1/2" chuck with key, 3-1/2" angle vise and safety guard



Model No. TS208
Mfg. No. KC-40HS
Chuck size: 1/2"
Speeds: 6 (60-1500 RPM)
Table size: 21-3/4" x 19-1/2"
Spindle Taper: #3 Morse
Motor: 1.5 HP, 11 A
Voltage: 220 V, 1 phase, 60 Hz
Dimensions: 21-1/4" L x 30" W x 78" H
Weight: 575 lbs.
Price/Each \$

28" Variable Speed Gearhead Drill Presses

- Quill has an internal MT#4 to accept tapered drill press accessories
- Feed selector dial and automatic power down-feed lever
- Production sized table with coolant collector
- 1/8 HP coolant pump built-in
- Positive depth stop for quick, easy adjustment



Model No. TDX416
Mfg. No. KC-50
Chuck size: 5/8"
Speeds: 2-range, variable (60-870 and 120-1740)
Table size: 22" x 22"
Spindle taper: #4 Morse
Motor: 2 HP
Voltage: 550 V, 3 phases, 60 Hz
Dimensions: 22" L x 37" W x 91" H
Weight: 1012 lbs.
Price/Each \$