

## Mini Milling & **Drilling Machine**

- Powerful, 3/4 HP, single-phase DC motor
- Variable speed gear drive
- Spindle depth fine feed control with micro downfeed dial
- Emergency stop button
- Includes: 1/2" chuck, chuck key, R8-JT#33 chuck arbor, chuck guard, 2 T-slot nuts, oil bottle, adjustment wrenches and hex keys



UAD693 Model No. Mfg. No. KC-15VS Drilling Capacity: 1/2" Max. distance spindle 11-1/4"" nose to table: Speeds: Face mill capacity: 1-1/8" End mill capacity: 5/8" Working area of the table: 3-5/8" x 15-3/4" Size of T-slot on table: 7/16" **Dimensions:** 19-1/2" x 22" x 30" Price/Each

## **Milling Drilling Machine** with Digital Readout

- Comes with 1/2" chuck, chuck key, R8 chuck arbor, safety guard, 2 T-bolts, oil bottle, adjustment wrenches, hex keys and tool box
- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Spindle depth digital readout and control panel with metric and imperial readings
- Forward/reverse switch and variablespeed selector dials



Model No. TMA116 KC-20VS-2 Mfg. No. 5/8" **Drilling capacity:** No. of Speeds: 2 **Table Size:** 7-1/16" W x 27-1/2" L x 2-1/2" H **Overall Width::** 29-5/8" Overall Length: 27-1/2" Overall Height: 35-3/8' Price/Each \$

## **Gearhead Milling Drilling Machines**

- Spindle is equipped with four heavy-duty tapered roller bearings
- Forward and reverse switch
- Head tilts 90° to the left and 30° to the right
- Includes: 1/2" chuck with key, 3-1/2" angle vise and safety guard



Model No. BV698 Mfg. No. KC-40HC Drilling capacity: 1-1/4" Diameter of column: 4-1/2" 6 (60-1500 RPM) Speeds: Table size: 23" x 7-1/2" Size of T-slot on table: 1/2" 1.5 HP, 11 A, 1 phase, 60 Hz Motor: Voltage: 220 V **Dimensions:** 38" L x 37" W x 78" H Approx. shipping weight: 630 lbs.

## **Milling Drilling Machines**

- Spindle is equipped with four heavy-duty tapered roller bearings
- Table control hand wheels have large micrometer dials graduated in 0.001"
- Head swivels 360° and is easily raised and lowered
- Includes: 3" face cutter, 1/2" chuck with key, 3-1/2" angle vise and safety guard



Model No. Mfg. No. Drilling capacity: Diameter of column: 12 (150-2500 RPM) Speeds: . Working area of table: 8-1/4" x 28-3/4" Size of T-slot on table: 11 A @ 220 V, Motor:

1 phase, 60 Hz Voltage: 110/220 V Pre-wired at: 110 V Dimensions: 43" L x 39" W x 42" H Approx. shipping weight: 600 lbs. Price/Each



**ACCESSORY** Model No. Mfg. No. Description **Dimensions** Price/Each



TS221 SS-45 Optional stand for TS218 31" x 21-1/2" x 28-1/4"

Price/Each

TS218

PDM-30

1-1/4"

4-3/4"

5/8'