7" x 12" Metal Cutting **Dual Swivel Bandsaws**

- Head swivels 0° 45° to the left and right
- Adjustable ball bearing guides
- Portable design for easy movement
- Coolant system
- Automatic shut-off switch
- Adjustable hydraulic downfeed control



TBU410 Model No. Mfg. No. KC-712DS Cutting capacity at 90°: Rect. 7" x 12", Round 7" Rect. 3-1/2" x 5-1/2", Round 5" Cutting capacity at 45°: Speeds: 4 (98, 164, 246, 328 FPM) 0.75" x 0.032" x 93" Blade: 1 HP, 6.2 A, 1 phase, 60 Hz Motor: Voltage: 220 V **Dimensions:** 50" L x 26" W x 44" H 325 lbs. Weight: Price/Each

10" x 18" Metal **Cutting Bandsaws**

- Carbide ball bearing blade guides
- Centralized 24 V control panel and automatic shut-off
- Adjustable hydraulic down feed control
- Tru-Lock™ cam lock and quick positioning vise system with fully adjustable jaws for 0° to 45° angled cuts
- To ensure reliable accurate cuts, both adjustable control arms can be positioned as close to the cut as possible
- Coolant system with regular valves provide an even flow of coolant to the blade

Model No. TLZ123 Mfg. No. KC-227-2 Cutting capacity at 90°: Rect. 10" x 18", Round 10" Rect. 7" x 9-3/8", Round 10" Cutting capacity at 45°: Speeds: 4 (114, 196. 288, 377 FPM) Blade: 122" x 1" x .032" 2 HP, 15 A, 1 phase, 60 Hz Motor Voltage: 220 V Dimensions: 70" x 27" x 42" 634 lbs. Weiaht:

TLZ124 KC-227-6 Rect. 10" x 18", Round 10" Rect. 7" x 9-3/8", Round 10" 4 (114, 196. 288, 377 FPM) 122" x 1" x .032" 2 HP, 2.6 A, 3 phase, 60 Hz 600 V 70" x 27" x 42" 634 lbs.

Ś

9" x 18" Metal Cuttina **Swivel Bandsaws**

- Carbide ball bearing blade guides with rollers
- Centralized control panel and automatic shut-off
- Adjustable hydraulic downfeed control
- Precision blade tension adjustment Quick-positioning vise with fully
- adjustable jaws for 0° to 45° angles
- Includes: Coolant system



Model No. TZ538 Mfg. No. KC-918S-V Cutting capacity at 90°: Rect. 9" x 18", Round 9' Rect. 9" x 11", Round 9" (80-250 FPM) variable Cutting capacity at 45°: Speeds: Blade: 131-3/4" x 1" x 0.032" Motor: 2 HP, 15 A, 1 phase, 60 Hz Voltage: 220 V **Dimensions:** 73" L x 32" W x 42" H Weight: 1070 lbs. Price/Each

10" x 18" Variable Speed Swivel **Metal Cutting Bandsaws**

- Swivel base from 0° to 45°
- Position adjustable control panel and automatic shut-off

Price/Each

- Adjustable hydraulic down feed control
- Carbide ball bearing blade guides
- To ensure reliable accurate cuts, both adjustable control arms can be positioned as close to the cut as possible
- Exclusive 24 V control panel
- Coolant system with regular valves provide an even flow of coolant to the blade

Model No. **TMA040** KC-228S-V-2 Cutting capacity at 90°: Rect. 10" x 18", Round 10" Cutting capacity at 45°: Rect. 7-7/8" x 7-7/8". Round 7-7/8" Speeds: (73-312 FPM) variable Blade: 121-3/4" x 1" x .035" Motor: 2 HP, 15 A, 1 phase, 60 Hz

Voltage: 220 V 81" x 28" x 48" **Dimensions:** Weight: 845 lbs.

Price/Each



Rect. 10" x 18", Round 10" Rect. 7-7/8" x 7-7/8", Round 7-7/8" (73-312 FPM) variable 121-3/4" x 1" x .035" 2 HP, 2.6 A, 3 phase, 60 Hz 600 V 81" x 28" x 48"

845 lbs.

18" Metal Cutting Bandsaws

- Hand wheel controls speed
- Speed changes while the machine is in operation
- Bandsaw blade welder and grinder included
- Includes: 4-way tilting table, and work light




Table size: Table tilt (all directions): Motor: Voltage:

Table height from floor: **Dimensions:** Weight:

Price/Each





Variable Speed Bandsaws

- Designed for both wood and metal cutting applications
- Variable frequency drive speed control and digital display for blade speed in feet/min
- Blade speed digital readout

Model No. TYP040 KC-1700WM-VS Mfg. No. Height of cut: 12" **Cutting capacity** frame to blade: 16-1/4" Blade size: 131-5/8" x (1/8"-1") x 1/32" Table size: 23-1/2" W x 17" L Motor: 2 HP Voltage: 220 V Amps: 7A Variable Speeds (Wood): 540-3600 SFPM 100-650 SPFM Variable Speeds (Metal): Overall dimensions: W x 30" L x 74" H Style: Vertical Price/Each



1015 lbs.