



Utility Hammers

- Ideal for structural maintenance and repair
- Air Consumption: 25 CFM
- Air Inlet: 1/4" NPTF
- Sound Level (dBA): 100



UAG272



UAG273



Model No.	Mfg. No.	BPM	Bore & Stroke	Cold Rivet Capacity	Head Material	Overall Length	Chisel Shank	Bore Diameter	Price /Each
UAG272	GS-0809BR	3000	3/4" x 2-5/8" (19.0mm x 66.0mm)	1/4" (6.4 mm)	Steel	7-1/2" (190 mm)	0.401" (Round)	3/4" ID (19.05 mm)	
UAG273	GS-0809AR	2200	3/4" x 3-5/8" (19.0mm x 92.0mm)	5/16" (7.9 mm)	Steel	9-13/16" (250 mm)	0.401" (Round)	3/4" ID (19.05 mm)	

Utility Hammers

For light to medium duty chipping, trimming, riveting, cutting, piercing & peening jobs

- Aluminum body
- 2 5/8" stroke (TG087), 3 1/2" stroke (TG088)
- Piston air-cushioned on return stroke
- 1/4" (NPTF) air inlet
- 3/8" minimum air hose size



TG087



TG088



Model No.	Mfg. No.	Capacity Cold Rivets in. (mm)		Bore and Stroke in. (mm)	Blows per Minute	Rivet Set and Chisel Shank	CFM	dBA	Vibration m/s ²	Overall Length in. (mm)	Net Weight lbs. (kg)	Price /Each
		Dural	Steel									
TG087	CP7111	1/4 (6.4)	3/16 (4.8)	3/4 x 2 5/8 (19 x 67)	3000	0.401 (10.19 mm)	25	100	8.9	6 3/4 (171)	3 1/2 (1.6)	
TG088	CP7150	5/16 (7.9)	1/4 (6.4)	3/4 x 3 1/2 (19 x 89)	2300	0.401 (10.19 mm)	25	100	9.4	8 7/8 (225)	4.2 (1.9)	

Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1.

Short Barrel Air Hammer

- Ideal for exhaust and front-end jobs, general bolt cutting, pin driving, and body shearing work
- Anti-vibration feature reduces tool vibration
- Ergonomic grip provides comfort for extended use
- Quick-change retainer allows for faster chisel changeovers
- BPM: 3500



Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Bore & Stroke	Price /Each
BARE TOOL						
UAJ235	123MAX	24.1 CFM	1/4" NPT	105.7	3/4" x 2-5/8" (19.05mm x 66.8mm)	KIT
UAJ386*	123MAXK	24.1 CFM	1/4" NPT	106	3/4" x 2-1/2" (19 mm x 89 mm)	

*Includes: Tool, Quick change retainer, and 5-piece chisel set.

Air Hammer

- Great for exhaust and front-end jobs, general bolt cutting, pin driving and body shearing work
- Optimized for the vehicle repair industry, heavy trucks, and MRO
- BPM: 2530



Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Bore & Stroke	Price /Each
BARE TOOL						
UAJ387	119MAX	23.8 CFM	1/4" NPT	106	3/4" x 3-1/2" (19 mm x 89 mm)	
KIT						
UAJ388*	119MAXK	23.8 CFM	1/4" NPT	106	3/4" x 3-1/2" (19 mm x 89 mm)	

*Includes: Tool, Quick change retainer, and 5-piece chisel set.