



Air Scribe® Pens

• Vibration level: 4.2 m/s²

INCLUDED ACCESSORIES:

- Air hose - 3/16" (5 mm) I.D.
- Air filter assembly
- Stylus - carbide tipped for writing and engraving
- Anvil for use with chisels and blank
- Flat chisel for scaling and deburring
- Chisel blank, customized to suit
- Round nose chisel for cleaning weld beads
- Carrying case



Model No.	Mfg. No.	Max Blows Per Minute	Weight lbs. kg	Length in. mm	Air Flow L/s CFM	Min Hose Bore in. mm	Sound Level dBA	Price /Each
AIR SCRIBE® KIT								
TCW246	CP9361-1 KIT	13 500	0.31 0.14	5 127	0.5 1.1	3/16 5	79	
TKZ813	POS4177			Replacement Stylus				

Compact Engraving Pens

- Finger tip start valve
- Fine point stylus
- Enhanced control
- Compact and lightweight
- Engraves at 32 400 BPM
- Quiet operation @ 59 dB(A)

Model No. THZ727
 Mfg. No. CP9160
 Price/Each \$



Pencil Grinders 60000 RPM

- High-speed air motor, controlled with patented governor, provides constant speed under load
- Precision, high-tolerance, low run-out collet. Run-out is a true 0.0002 @ 1" (25 mm) from face
- Super flexible hose for maximum agility

Model No. TGZ034
 Mfg. No. 51700
 Collet Insert Size: 1/8"
 Air Flow Rate @ 90 PSI: 8 SCFM
 Sound Level: 66 dB(A)
 Motor Characteristic: Oil-Less Turbine
 Free Speed: 60 000 RPM
 Bearing Type: Metal
 Exhaust Type: Rear
 Weight: 0.6 lbs.
 Packaged Weight: 1.6 lbs.
 Price/Each: \$



10-04 Series - Precision Pencil Grinders

- Tool weight: 0.2 lbs. • Tool length: 5.8"
- Motor power: 0.1 HP (0.074 kW)
- Industrial bearing provides long life expectancy
- Designed for precision deburring and metal removal
- Compact and light aluminum weight housing
- Roll throttle equipped
- Tool requires lubricated airline at 90 PSI maximum
- Air consumption: 9 CFM
- Air inlet: 1/8" • Sound level (dBA): 78
- Collet size: 1/8" • No load RPM: 60 000

Model No. TYL565
 Mfg. No. TOR0401-18
 Price/Each \$



15Z Series - Air Marking Pen

- Tool weight: 0.3 lbs. • Tool length: 5.5"
- Free speed: 20 000 RPM
- Abrasive capacity: 1/8" stylus
- Motor power: 0.06 HP (0.044 kW)
- Sliding sleeve throttle
- Ideal for marking a variety of materials, ranging from aluminum to titanium
- Carbide tipped stylus
- Engineered for heavy duty applications in the most demanding environment
- Air consumption: 9 CFM • Air inlet: 1/4"
- Sound level (dBA): 80

Model No. TYN251
 Mfg. No. 15Z-710
 Price/Each \$



12-10 Series - Inline Collet Grinders

- Tool weight: 0.8 lbs.
- Tool length: 6.0"
- Motor power: 0.3 HP (0.22 kW)
- Abrasive capacity: 1/2" carbide burr or 1" mounted wheel
- Durable and ergonomic composite housing
- Compact size for ultimate control - easy access to confined areas
- Ideal for die and mold work as well as deburring
- Standard equipped with lock-off lever
- Performance rated @ 90 PSI / 620 kPa air pressure
- Air consumption: 16 CFM
- Air inlet: 1/4"
- Sound level (dBA): 81
- Collet size: 1/4"
- No load RPM: 25 000



Model No.	Mfg. No.	Exhaust Location	Price /Each
TYL601	12L1003-36	Front	
TYL620	12L1082-36	Rear	

TYL601



10-90 Series - Precision Turbine Grinders

- Tool weight: 0.5 lbs. • Tool length: 5.4"
- Motor power: 0.06 HP (0.044 kW)
- Requires no air line lubrication - High precision ball bearings for long life expectancy
- Two-stage turbine motor with roll throttle
- Achieves a superb finish with its high speed and precision spindle
- Lightweight and durable aluminum housing
- Low vibration and quiet operation minimizes operator fatigue
- CAUTION: Use dry air at 90 PSI maximum: Do not lubricate turbine grinders. Lubrication will be detrimental to the operation and life of turbine tools
- Air consumption: 6 CFM • Air inlet: 1/8"
- Sound level (dBA): 75 • Collet size: 1/8"
- No load RPM: 100 000

Model No. TYL572
 Mfg. No. 10R9000-08
 Price/Each \$

