



## Regulators (Gauge Included)

- High performance
- Compact design allows for greater design flexibility
- **Heavy-Duty:** High-capacity performance featuring rugged design for the most demanding applications

**TOPRING**

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Reduced Pressure Range PSI	Max Temp. °F	Bowl Type	H"	W"	Price /Each
<b>MINI MODULAR DESIGN</b>									
TA644	1/4	40	300	0-125	125	Zinc	4 3/32	1 19/32	
TA645	1/4	40	300	0-125 (Non-Rel)	125	Zinc	4 3/32	1 19/32	
TA646	1/4	40	300	0-25	125	Zinc	4 3/32	1 19/32	
TA647	1/4	40	300	0-60	125	Zinc	4 3/32	1 19/32	
<b>COMPACT MODULAR DESIGN</b>									
TA648	1/4	25	300	0-125	125	Zinc	4 9/64	2 3/16	
TA650	1/4	25	300	0-25	125	Zinc	4 9/64	2 3/16	
TA651	1/4	25	300	0-60	125	Zinc	4 9/64	2 3/16	
TA652	3/8	45	300	0-125	125	Zinc	4 9/64	2 3/16	
TA655	3/8	45	300	0-60	125	Zinc	4 9/64	2 3/16	
TA656	1/2	60	300	0-125	125	Zinc	4 9/64	2 3/16	
<b>STANDARD DUTY MODULAR DESIGN</b>									
TA660	1/2	150	300	0-125	125	Aluminum	5 9/16	2 11/16	
TA661	1/2	150	300	0-125 (Non-Rel)	125	Aluminum	5 9/16	2 11/16	
TA664	1/2	150	300	0-250	125	Aluminum	5 9/16	2 11/16	
TA665	3/4	150	300	0-125	125	Aluminum	5 9/16	3 1/32	
TA666	3/4	150	300	0-125 (Non-Rel)	125	Aluminum	5 9/16	3 1/32	
<b>HEAVY-DUTY</b>									
BT861	3/4	300	300	5-250	125	Zinc	10 1/32	4 11/16	
TA670	1	400	300	0-125	125	Zinc	10 7/16	4 11/16	
TA672	1 1/2	500	300	0-125	125	Zinc	10 11/32	4 15/16	



Mini TA644



Medium Duty TA648



Heavy-Duty TA670

## Lubricators

- High performance over a wide flow range
- Easy maintenance
- Compact size

**TOPRING**

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Max Temp. °F	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
<b>MINI MODULAR DESIGN</b>									
TA675	1/4	45	150	125	Polyurethane	1.5	5 3/4	1 19/32	
<b>COMPACT MODULAR DESIGN</b>									
TA677	1/4	15	150	125	Polyurethane w/guard	3.8	6 15/16	2 3/16	
TA679	3/8	80	150	125	Polyurethane w/guard	3.8	6 15/16	2 3/16	
TA681	1/2	80	150	125	Polyurethane w/guard	3.8	6 15/16	2 3/16	
<b>STANDARD DUTY MODULAR DESIGN</b>									
TA683	1/2	110	150	125	Polyurethane w/guard	8.5	8 9/16	2 11/16	
TA684	1/2	110	250	150	Zinc	8.5	8 9/16	2 11/16	
TA685	3/4	125	150	125	Polyurethane w/guard	8.5	8 9/16	3 1/32	
TA686	3/4	125	250	150	Zinc	8.5	8 9/16	3 1/32	



Mini w/Polyurethane Bowl TA675



Standard w/Zinc Bowl TA684

## Air Tool Oil

Air Tool Oil is specially formulated to preserve and maintain the internal seals and mechanisms present in most hand held air tools. Air Tool Oil lubricates under high pressure to fine tolerances and resists moisture induced corrosion, maximizing the service life and performance of your air tools. Air Tool Oil contains no silicone.

**Lloyds**

Model No.	Container	Price /Each	Qty	Qty Price /Each
AA091	8-oz. poly bottle			
AA090	4-litre jug			



## Air Tool Oil

- Ideal for keeping pneumatic equipment operating longer with greater power and less down time
- Formulated using a quality base lubricant and a high-tech additive system
- 448-ml bottle

Model No. AF107  
Price/Each \$

