

Red & Redi Multi-**Purpose Red Grease**

- Delivers excellent lubrication
- Prevents rust, corrosion and oxidation
- Remains effective at extremely high temperatures
- Reduces friction and vibration
- Resists shock
- Red colour allows easy visual inspection
- Penetrates quickly
- Non-melting



Model	Mfg.		Price	Qty Price	
No.	No.	Size	/Each	Qty	/Each
ΛΛ972	C05016	11 07			

White Lithium Grease w/PTFE

- Rapidly forms into a pure white grease
- Heat and water resistant
- Produces a long lasting. protective film against rust and corrosion
- White colour allows easy visual inspection
- Does not contain any chlorinated solvents
- Accepted for use in Canadian food processing facilities



Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AA914	C03816	10 oz.			

LU100 White Lithium Grease

- · Inhibits corrosion on unpainted metal surfaces
- High-solids, non-staining white grease
- Excellent for metal-to-metal applications
- Will not drip or run on vertical surfaces
- Effective from -20°F to 275°F
- For chains, gears, drives, hinges and other vertical or overhead surfaces
- Recommended for use on knockout pins on mould equipment
- NSF registered category code H2



Model	Mfg.		Price	Qty	Price
No.	No.	Size	/Each	Qty	/Each
ΔΔ103	SC0100000	11 07			

ViperLube™ High **Performance** Synthetic Grease

- Grease provides superior protection against equipment exposed to a wide range of operating temperatures and environments
- Use as a lubricant and protective anti-rust film on bearings, machine parts, equipment, or as a release agent on gaskets and seals
- Temperature resistance: 400°F (204°C) continuous
- NLGI Grade: 2/Severe Duty GC-LB
- NSF registered category code H1
- Accepted for use in Canadian food processing facilities



LOCTITE.

Model	Mfg.		Price	Qty Pri	
No.	No.	Size	/Each	Qty	/Each
AB505	457456	3 oz.			
AB508	457457	14 oz.			
AB507	457458	400 g.			
AE853	1906102	10.1 oz.			
AB509	459782	30 lbs.		-	-

Dielectric Grease

- Moisture proof barrier that lubricates and protects electrical equipment from salt, dirt, and corrosion
- High dielectric strength Good thermal, oxidation and chemical stability
- Temperature resistance: 400°F (204°C) continuous



LOCTITE

Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AC365	270640	0.33 oz.			

Multi-Purpose Concrete

Repair & Adhesive

Excellent for bridging horizontal or

vertical cracks, even under water

Twice as strong as concrete

For indoor or outdoor use

brick, steel and more

Colour: Light Gray

Works on concrete, masonry,

White Lithium Grease

- For metal-to-metal and metal-to-plastic applications
- Corrosion protection
- No ODC's
- Temperature resistance: 380°F (193°C) dropping point



LOCTITE

Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AA611	270638	1.5 oz. tube			
AE854	1906122	10.75 oz. Aerosol			

Clear Penetrating Grease

- Protects against corrosion Resists water washout
- Quick penetrating action
- High tack
- Metal detectable plastic components-DETEXT



RUST-OLEUM

Model No.	Mfg. No.	Size	Pric /Eacl
KP497	257395	9 oz.	
KP498	257397	Replacement Static Mixers - 3 Pack	

Turbokrete Concrete Patch Compound Kits

- Easily repair deep holes and cracks
- 100%-solids epoxy patch kit is designed for floors exposed to heavy traffic and intermittent chemicals
- Protects against abrasion, impact and most chemicals—no sealer required
- Creates an extremely hard surface—3-4 times stronger than concrete
- For interior/exterior use on damaged or severely spalled floors, curbs, ramps, etc.
- Odorless
- Easy-mix kit includes base, activator and aggregate
- Colour: Light Gray



RUST-OLEUM

Model No.	Mfg. No.	Size	Price /Each
KP495	253479	2 gal.	
KP496	5494323	3.5 gal.	



Model	Mfg.		Price	(ty Price
No.	No.	Size	/Each	Qty	/Each
AD479	C06716	11 oz.			