



Quick-Grip® C-Clamps

- Double-rolled thread for faster clamping and increased durability
- Larger handle for greater clamping pressure with less effort and reduced hand fatigue
- Larger swivel pad reduces marring on work surface and increases stability



Model No.	Mfg. No.	Clamping Capacity	Throat Depth	Price /Each
TBR751	225101	1" (25 mm)	1 3/16" (30 mm)	
TBR752	225102	2" (50 mm)	1 5/16" (33 mm)	
TBR753	225103	3" (75 mm)	2 1/4" (51 mm)	
TBR754	225104	4" (10 cm)	3" (75 mm)	
TBR755	225106	6" (15 cm)	3 1/2" (87 mm)	
TBR756	225108	8" (20 cm)	4" (10 cm)	
TBQ959	225123	2" (50 mm)	3 1/2" (87 mm)	
TBQ960	225134	3" (75 mm)	4 1/2" (12 cm)	

Economy C-Clamps

- Reinforced at all stress points designed to last through the toughest application
- Constructed of high quality ductile iron with a heavy-duty steel screw for maximum strength
- Fully enameled for long life



Model No.	Mfg. No.	Clamping Capacity"	Throat Depth"	Price /Each
VE830*	450-0761	1	1	
VE831*	450-0762	2	1 1/2	
VE833	450-0763	3	1 3/4	
VE834	450-0764	4	2 3/8	
VE835	450-0765	5	2 1/2	
VE836	450-0766	6	2 3/4	
VE837	450-0768	8	3 3/8	
VE838	450-0769	2 1/2	4 3/8	

* Constructed of malleable iron

C-Clamps

- Drop forged steel frame
- Lead screw and pad are copper plated to resist welding splatter
- Limited lifetime warranty



Model No.	Mfg. No.	Clamping Capacity	Throat Depth	Clamping Force lbs.	Overall Dimensions			Weight lbs.	Price /Each
					L"	x W"	x H"		
TYQ473	C402	2" (50 mm)	1-3/4" (44.45 mm)	3500	7-1/2	x 5	x 1-1/4	1.4	
TYQ474	C403	3" (76 mm)	2-1/2" (63.5 mm)	3500	8-1/4	x 6-1/2	x 2	2.2	
TYQ475	C404	4" (102 mm)	3" (76.2 mm)	6200	11	x 6	x 1	3.3	
TYQ476	C408	8" (203 mm)	4-1/2" (114.3 mm)	6900	15	x 8	x 2	7.4	
TYQ477	C412	12" (305 mm)	5-1/2" (139.7 mm)	9300	22-1/2	x 10-1/2	x 2	12.75	

Hi-Vis Safety C-Clamps

- Coated in high visibility yellow
- Powder coat finish resists scratches and corrosion
- Alloy steel spindles, black oxide coated



Model No.	Mfg. No.	Clamping Capacity"	Throat Depth"	Price /Each
TJW241	14300	2-1/8	2-1/4	
TJW242	14301	3	1 1/2	
TJW244	14303	6-1/16	4-1/8	
TJW245	14305	8-1/4	5	
TJW246	14306	10-1/8	6	
TJW247	14307	12-1/4	6-5/16	

C-Clamps

- Manufactured from SG iron with over 60000 PSI of tensile strength
- Swiveling pad adapts to the correct angle to apply even pressure on the work piece
- Textured powder coat finish on frame and black oxide finish on spindle increases corrosion resistance



Model No.	Clamping Capacity"	Throat Depth"	Min. Proof Test lbs.	Price /Each
TYB502	2	1 5/8	800	
TYB503	3	1 11/16	1000	
TYB504	4	2 11/32	1200	
TYB505	6	3	1400	
TYB506	8	3 1/8	1700	
TYB507	10	3 1/2	2200	
TYB508	12	4	2500	