



WP-17

High Capacity for Thin to Medium Gauge Materials

- Compact and durable for field welding applications
- Ribbed handle for comfort and cool operation
- Finger tip gas control valve on WP-17V
- Torch body head: 70° angle
- Torch length: 7 3/4"
- Max capacity: 150 A
- Handle style: Ribbed



WP-17

WP-26

Maximum Capacity for Continuous Heavy-Duty Use

- Heavy copper construction for rugged field work
- Torch body head: 70° angle
- Torch length: 8 1/2"
- Max capacity: 200 A
- Handle style: Ribbed



WP-26



WELDCRAFT



Model No.	Weldcraft Mfg. No.	Price /Each	Model No.	Weldmate Mfg. No.	Price /Each	Model No.	C-K Mfg. No.	Price /Each
366-4669	WP-24					820-1590	CK80	
TTT271	WP-24F					820-1615	CK90	
TTT272	WP-24FV					820-2070	CK90V	
TTT273*	WP-24-25-R							
TTT275*	WP-24F-25-R		363-1945	VT-9F-25-R				
TTT276*	WP-24FV-25-R		363-1970	VT-9FV-25-R				
366-4249	WP-9					820-2205	CK130V	
366-4378	WP-9V							
366-4278	WP-9F							
366-4300	WP-9FV							
366-4402*	WP-9-25-R					820-2270	CK1325H RG	
366-4399*	WP-9V-25-R					820-2105	CK1325VH RG	
TTT277*	WP-9F-25-R							
366-4324*	WP-9FV-25-R					820-2090	CK1325VH FX	
366-4438	WP-17					820-1115	CK150 RG	
366-4513	WP-17V					820-1125	CK150V RG	
366-4462	WP-17F					820-1110	CK150 FX	
366-4486	WP-17FV					820-1120	CK150V FX	
NP473	WP-17-25-2					820-1200	CK1525VN RG	
NP474	WP-17V-25-2					820-1165	CK1525H RG	
366-4459*	WP-17-25-R					820-1185	CK1525VH RG	
366-4540*	WP-17V-25-R							
366-4483*	WP-17F-25-R					820-1180	CK1525VH FX	
366-4510*	WP-17FV-25-R							
366-4744	WP-26		363-1280	VT-26		820-1280	CK210-R / CK26 RG	
366-4822	WP-26V		363-1640	VT-26V		820-1290	CK210V-R / CK26V RG	
366-4774	WP-26F		363-2025	VT-26F		820-1275	CK210-F / CK26 FX	
366-4795	WP-26FV		363-2050	VT-26FV		820-1285	CK210V-F / CK26V FX	
NP476	WP-26V-25-2		363-1220	VT-26-25-2				
366-4765*	WP-26-25-R		363-1455	VT-26V-25-2		820-1355	CK2125H-R / CK26-25-R RG	
366-4843*	WP-26V-25-R		363-1435	VT-26-25-R		820-1390	CK2125VH-R / CK26V-25-R RG	
366-4792*	WP-26F-25-R		363-1460	VT-26V-25-R		820-1350	CK2125H-F / CK26-25-R FX	
366-4819*	WP-26FV-25-R		363-2045	VT-26F-25-RFX		820-1380	CK2125VH-F / CK26-25-R FX	
			363-2070	VT-26V-25-RFX				

* Power cable adapter must be ordered separately