

Defense Anti-Freeze & Pump Lubricants

- Provides year round pump protection for water coolers and closed loop water systems
- Contains a lubricant additive providing continuous pump lubrication during operation
- Prolongs seal and shaft life because of its silicate free formula
- Protects from freezing to -30°F when undiluted (a dilution of two parts Defense to one part water protects to -10°F) except for pre-mixed formula, protects to 10°F

Note: Although Defense is a permanent anti-freeze and pump lubrication solution, it should be changed annually to maintain maximum anti-freeze protection and pump lubrication.



| Model | Mfg. | | Price |
|----------|-----------|-----------------------|-------|
| No. | No. | Size | /Each |
| 881-1355 | DF927-PM | 1 Gallon, Pre-Mixed | |
| 881-1350 | DF929-4x1 | 1 Gallon | |
| 881-1365 | DF929-5 | 2 Jugs of 2.5 Gallons | |
| 881-1370 | DF929-55 | 55-Gallon Drum | |



881-1355

881-1350

Spray Galv/Cold Galv

ZINC GALVANIZING COATING

- Produces hard zinc coating that will stop rust and corrosion on all metal surfaces
- Compounded from 95.1% metallic zinc dust
- Equal to hot dip galvanizing in cathodic protection and film durability
- Meets or exceeds military specs



| Model | Mfg. | | | Price |
|----------|-----------|-------------|------------------------|-------|
| No. | No. | Description | Size | /Each |
| 877-1125 | DF309-16 | Spray Galv | 13-oz. Net Wt. Aerosol | |
| 877-1130 | DF306-6x1 | Cold Galv | 1 Quart | |
| 877-1120 | DF306-2x1 | Cold Galv | 1 Gallon | |





877-1120

877-1125

Spotcheck® Penetrants

- Red visible non-destructive test method which provides for the detection of surface discontinuities (flaws) in ferrous and non-ferrous test materials
- Ideal for applications where portability is required
- Vivid red colour permits daylight inspection

MAGNAFLUX

NP701 **TTU436** NP703 NP702 SPOTCHECK SKD-S2

SKL-SP2 PENETRANTS

- Exhibits outstanding penetrating characteristics, which provide for maximum reliability in locating surface-open flaws and discontinuities
- Can be used over the entire spectrum of industrial applications, where a visible penetrant inspection system meets the requirements for surface-open flaw detection
- Has also been successfully used on non-porous ceramics and similar materials
- Not recommended for the inspection of plastic materials, as it may stain, soften or even dissolve the base material under test
- Should be used at temperatures between 40°F-125°F

| Model | Mfg. | Size | Price |
|-------|------------|----------------|-------|
| No. | No. | | /Each |
| NP701 | 01-5155-78 | 16-oz. Aerosol | |

SKL-WP2 WATER WASHABLE PENETRANTS

General purpose

| Model | Mfg. | Size | Price |
|--------|------------|----------------|-------|
| No. | No. | | /Each |
| TTU436 | 01-5190-78 | 16-oz. Aerosol | |

SKC-S SOLVENT CLEANERS

- Non-chlorinated cleaner/remover
- Used as a precleaner, a post cleaner and a penetrant remover
- Recommended general purpose
- Meets major requirements for special alloy and nuclear applications

| Model | Mfg. | Size | Price |
|-------|------------|----------------|-------|
| No. | No. | | /Each |
| NP703 | 01-5750-78 | 16-oz. Aerosol | |

SKD-S2 SOLVENT DEVELOPERS

- Ready-to-use suspension of white developing particles in a fast drying solvent
- Non-chlorinated solvent developer
- Meets major requirements for special alloy and nuclear applications

| Model | Mfg. | | Price |
|-------|------------|----------------|-------|
| No. | No. | Size | /Each |
| NP702 | 01-5352-78 | 16-oz. Aerosol | |

Ardrox®

9D1B NON-AQUEOUS DEVELOPERS

- Liquid product consisting of a finely divided white powder dispersed in a non-halogenated volatile solvent system
- Can be used with Type I (fluorescent) and Type II (visible) penetrants

906 WATER WASHABLE VISIBLE PENETRANTS

- Visible penetrants are not rated by sensitivity but are generally considered to be equivalent to Level 1
- Provides low cost, crisp indications, low residual background and temperature stability
- Used with non-aqueous developers or aqueous developers
- May be applied by aerosol, brushing, tank immersion, conventional, electrostatic or spraying

9PR50 CLEANERS/REMOVERS

- Quick drying, non-halogenated (non-chlorinated) solvent for removing oil, grease and similar soils from metal surfaces
- Provides a high level of cleaning efficiency with operational safety
- Corrosion safe for use on both ferrous and non-ferrous alloys
- Excellent penetrant remover



| Model | Mfg. | | Price | |
|-------------------------|-----------|----------------|-------|--|
| No. | No. | Size | /Each | |
| 9D1B NO | N-AQUEOU: | S DEVELOPERS | | |
| 874-1150 | 9D1B-16 | 16-oz. Aerosol | | |
| 906 PENI | ETRANTS | | | |
| 874-1080 | 906-16 | 16-oz. Aerosol | | |
| PPR50 CLEANERS/REMOVERS | | | | |
| 874-1180 | 9PR50-16 | 16-oz. Aerosol | | |
| | | | | |