

EL601 Red Insulating Varnish

- Insulating spray for general coating, impregnating and insulating electrical and electronic work
- Resists oil, water, acids and alkalis
- Excellent adhesion
- Oil resistant per ASTMD-115-55



Model	Mfg.		Price	Qty Price
No.	No.	Size	/Each	Qty /Each
ΔΔ179	SC0601000	15 25 nz		

SP603 Blue Layout Dye

- Applies a smooth, even
- coat for all layout workFast-drying, non-flaking, non-etching, won't peel
- Adheres to metal or glass
- For pattern-making, tool and die making, machining and maintenance
 mechanicals





Model	Mfg.		Price	Qty Price
No.	No.	Size	/Each	Qty /Each
A A180	200603000	12 07		

SP606 Layout Dye Remover

- Removes layout fluids quickly and efficiently
- Removes light oils, greases, lacquer and other markings on metal or glass
- Leaves no residue
- · No chlorinated solvents
- For tool and die making and production departments



Model	Mfg.		Price	Qty Price	
No.	No.	Size	/Each	Qty /Each	
AA181	SC0606000	12 75 07			

Cutting Oil Thread Cutting Lubricant

- Ideal for use on all types of metals, including brass, copper and aluminum
- NSF Registered P1





Model	Mfg.		Price	Qty Price
No.	No.	Size	/Each	Qty /Each
AF250	73500	340 a		

A-9 Aluminum Cutting Fluids

- Designed for aluminum, non-ferrous metals
- Forms an effective extreme pressure boundary lubricant between tool and work surface
- Leaves a surface, which requires only ordinary cleaning



RELTON

Model	Size	Price	Qty Price
No.		/Each	Qty /Each
AA149	4 07.		

Rapid Tap™ Cutting Fluids

- Effective on tough-to-drill metals and alloys such as beryllium, molybdenum, stainless steel and stellite
- Makes tapping, reaming, drilling and threading operations easier, faster and more accurate
- Not recommended for use with aluminum and its alloys



RELTON

Model		Price	Qty Price		
No.	Size	/Each	Qty /Each		
AA160	4 oz.				

Coolcut™

- Extends cutting tool life
- · Suitable for all ferrous and non-ferrous metals
- · Produces a better finish
- Solvent-free, no chlorine
- For drilling, sawing, milling, turning, reaming, broaching





Sorrace recimologies						
Model No.	Description	Size	Price /Each	Qty	Qty Price /Each	
AA468	Liquid	350 ml				
AG673	Liquid	3.78 L				
AA470	Liquid	20 L				
AB748	Liquid	208 L				
AA471	Stick	300 g				
AA467	Aerosol Spray	400 ml				
AE955	Trigger Spray	500 ml				

AluCut™ Aluminum Cutting Lubricant

- High-performance lubricant that extends cutting tool life
- Specially formulated for use with aluminum and other non-ferrous metals
- Clean, precise, stain-free application
- Ideal for inclined, vertical, and overhead surfaces
- Coats cutting edge or workpiece
- Applications include cutting with circular chopsaws, sawing with jigsaws or portable bandsaws, drilling, nibbling, and tapping





Model No.	Description	Size	Price /Each	Qty	Qty Price /Each
AA191	Stick	300 a			

Coolcut™ S-30 Water-Miscible Cutting Lubricant

- Ready-to-use, high-performance metal cutting lubricant specially designed for automatic and semiautomatic metal removing operations
- Will not gum up slides and glides
- Increases feed, speed, and production
- Prevents bacterial growth when not in use
- Formulated with extended corrosion protection
 Contains extreme pressure additives (EP), bacterial control ingredients, and no chlorine
- Can be diluted up to 1:30



WALTER
Surface Technologies

Model No.	Description	Size	Price /Each	Qty	Qty Price /Each
AG516	Jug	3.78 L			
AF006	Jug	20 L			
AF007	Drum	208 L			