



## Torcofix Torque Wrenches

- Robust torque wrench with square drive and integrated ratchet head function for controlled bi-directional tightening
- Serial number on the wrench and the provided certificate allow for unambiguous product identification
- Mushroom head prevents an unintentional pulling out of the whole square drive when changing the nut socket
- Locking button enables reliable locking of the torque setting
- Ergonomically shaped, black plastic handgrip with calibration aid
- Micrometre scale for main N.m scale for setting interim values
- Dual scale N.m and ft-lbs. below a window with a magnifying glass effect
- Release system triggers a tactile and audible signal
- Guaranteed precision of  $\pm 3\%$  on the scale set torque



**GEDORE**

| Model No. | Mfg. No. | Overall Length" | Drive Type  | Torque Range                     | Increments            | Price /Each |
|-----------|----------|-----------------|-------------|----------------------------------|-----------------------|-------------|
| UAG329    | 2201429  | 8-3/4           | 1/4" Square | 0.75 - 3.7 lbf. Ft, 1 - 5 N.m    | 0.25 Nm, 0.25 ft-lbs. |             |
| UAG330    | 1545132  | 11-1/4          | 1/4" Square | 3.7 - 18 lbf. Ft, 5 - 25 N.m     | 1 Nm, 1 ft-lbs.       |             |
| UAG331    | 1545140  | 13              | 1/4" Square | 10 - 50 N.m, 7.5 - 37 lbf. Ft    | 2.5 Nm, 2.5 ft-lbs.   |             |
| UAG337    | 7674330  | 27              | 3/4" Square | 60 - 300 lbf. Ft, 80 - 400 N.m   | 10 Nm, 10 ft-lbs.     |             |
| UAG338    | 7674760  | 37-1/2          | 3/4" Square | 110 - 550 N.m, 80 - 405 lbf. Ft  | 10 Nm, 10 ft-lbs.     |             |
| UAG339    | 1521365  | 48-1/2          | 3/4" Square | 110 - 550 lbf. Ft, 150 - 750 N.m | 10 Nm, 10 ft-lbs.     |             |



UAG332

UAG333

UAG341

UAG342

### REPLACEMENT MUSHROOM HEAD DRIVES

| Model No. | Mfg. No. | Drive Connector Square (Female) | Drive Connector Square (Male) | Price /Each |
|-----------|----------|---------------------------------|-------------------------------|-------------|
| UAG332    | 1545167  | 3/8" (10 mm)                    | 1/4" (6.3 mm)                 |             |
| UAG333    | 1566385  | 3/8" (10 mm)                    | 3/8" (10 mm)                  |             |
| UAG341    | 7079370  | 1/2" (12.5 mm)                  | 1/2" (12.5 mm)                |             |
| UAG342    | 7079450  | 1/2" (12.5 mm)                  | 3/8" (10 mm)                  |             |

## Industrial Breaking Torque Wrenches

- Robust, all steel construction with corrosion-resistant finish is ideal for the automotive, bus and truck, chemical, energy and nuclear industries, as well as major construction and engineering projects
- Adjustability is provided by calibrated scales that allow the user to adjust the tool to their desired torque setting, enabling a range of different torque settings to be applied
- A visible micrometer style scale allows the user to adjust the tool quickly and easily to their desired torque setting
- Breaking mechanism reduces the risk of incorrect tightening
- Dual scales (N.m and lbf.ft)
- Supplied with an ISO 6789 calibration certificate and storage case



UAF439

**GEDORE**

| Model No. | Mfg. No. | Overall Length" | Drive Type  | Torque Range                      | Repeatability | Price /Each |
|-----------|----------|-----------------|-------------|-----------------------------------|---------------|-------------|
| UAF438    | 3022854  | 44              | 3/4" Square | 100 - 500 lbf. Ft, 150 - 700 N.m  | +/- 4%        |             |
| UAF439    | 3022862  | 43-7/8          | 3/4" Square | 150 - 600 lbf. Ft, 200 - 800 N.m  | +/- 4%        |             |
| UAF440    | 3022870  | 54              | 3/4" Square | 200 - 750 lbf. Ft, 300 - 1000 N.m | +/- 4%        |             |

## Dremometer Torque Wrenches

- Precision torque wrench for lots of different applications
- Long service life even when subjected to extreme continuous use
- Excellent design for safe, fault-free use
- Easy, user-friendly torque adjustment for reliable working
- Non-losable hexagon key in the handgrip
- Strong, high-strength yet light, long-lasting aluminium alloy
- All dremometer models come with a test certificate to DIN EN ISO 6789:2003.
- Two scales on each dremometer indicate N.m and the common US unit of torque measurement
- Guaranteed precision of  $\pm 3\%$  on the scale set torque



UAG451

**GEDORE**

| Model No. | Mfg. No.        | Overall Drive Length" Type | Torque Range                 | Increments        | Price /Each |
|-----------|-----------------|----------------------------|------------------------------|-------------------|-------------|
| UAF442    | 777544010-35/64 | 1/4" Square                | 6 - 30, 50 - 270 in-lbs.     | 1 N.m/10 in-lbs.  |             |
| UAF445    | 768200013-5/16  | 3/8" Square                | 8 - 40, 70 - 350 in-lbs.     | 5 N.m/50 in-lbs.  |             |
| UAF449    | 768332018-3/16  | 1/2" Square                | 25 - 120, 18 - 90 ft-lbs     | 5 N.m/5 in-lbs.   |             |
| UAF451    | 768553021-11/16 | 1/2" Square                | 40 - 200, 30 - 150 ft-lbs    | 5 N.m/5 in-lbs.   |             |
| UAF456    | 768545024-19/64 | 1/2" Square                | 60 - 300, 45 - 220 ft-lbs    | 5 N.m/5 in-lbs.   |             |
| UAF460    | 768847028-15/64 | 3/4" Square                | 80 - 360, 60 - 260 ft-lbs    | 5 N.m/5 in-lbs.   |             |
| UAF464    | 142715631-31/32 | 3/4" Square                | 110 - 550, 80 - 400 ft-lb    | 10 N.m/10 in-lbs. |             |
| UAF467    | 769150031-31/32 | 3/4" Square                | 155 - 760, 115 - 560 ft-lbs  | 10 N.m/10 in-lbs. |             |
| UAF473*   | 767018031-31/32 | 3/4" Square                | 155 - 760, 115 - 560 ft-lbs  | 10 N.m/10 in-lbs. |             |
| UAF477*   | 769401031-31/32 | 3/4" Square                | 520 - 1000, 380 - 730 ft-lbs | 10 N.m/10 in-lbs. |             |

\* Includes: (1) ALU extension tube (762 mm)

## M12 Fuel™ Digital Torque Wrench Kits

- PowerState™ brushless motor
- One-Key™ technology allows for customization, tracking, tool security, and inventory management
- Adjustable run-down torque to control the tool's output torque via the motor to prevent over torque
- RedLink Plus™ Intelligence enables advanced communication between batteries and tools
- Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory)
- Six pre-programmed languages including English, Spanish and French
- Durable design to withstand the most demanding jobsite environments
- Includes: (2) M12™ Redlithium™ CP2.0 battery packs, (1) M12™ Lithium-ion battery charger, (1) Carrying case, (1) Calibration certificate
- Voltage: 12 V
- Tool Accuracy: CW
- Ratcheting Angle: 4.5°
- RPM: 0 - 100
- Measuring Units: ft-lbs, in-lbs., N.m, kg-cm



UAI587

**Milwaukee**

| Model No. | Mfg. No. | Anvil Size Ball Detent" | Torque Range       | Length" | Price /Each |
|-----------|----------|-------------------------|--------------------|---------|-------------|
| UAI587    | 2465-22  | 3/8                     | 10 - 100 ft-lbs.   | 23.3    |             |
| UAI588    | 2466-22  | 1/2                     | 12.5 - 150 ft-lbs. | 23.5    |             |