(T CRESCENT

CRESCENT

Replacement Cutterhead

Mfg.

No.

(CRESCENT

CRESCENT

Replacement Cutterhead

Mfg.

No.

0513RBJ

Model

TBG065

No.

Price

/Fach

H.K. PORTER

Price

/Each

Model

No.

Price

/Each

H.K. PORTER

Price

/Each

Heavy-Duty Cutters

- Recommended for the most demanding hand cutting applications
- Heavy-duty straps support the jaws
 Maximum hardness of material to be cut:
- Brinell 455/Rockwell C48
- Lockplate keeps jaws from loosening
 Toggle joints turn 50 lbs. hand pressure to 4000 lbs. cutting pressure
- Screw-type adjustment realigns edges
 Available with tubular steel or lightweight, fibreglass handles

Model	Mfg.	Wt.	Overall Length		Hard N (Up to B	y Capacity Naterials rinell 455, rell C48)	Price	Replacement Cutterhead Model Mfg. Price			
No.	No.	lbs.	in.	mm	in.	mm	/Each	No.	No.	/Eac	
TBF968 TBG043	0190MCX 0390MCX	5.5 14.2	24 36	610 914	5/16 7/16	8 11		TBF946 TBG020	0113CX 0313CX		
LIGHTV	VEIGHT, FIB	ERGLAS	S HAN	IDLES							
TBF964	0190FCX	5.5	24	610	5/16	8		TBF946	0113CX		

Bolt Cutter/Cable Cutters

- Cuts soft, medium hard, and hard materials
- Cuts metal rod to 7/16" diameter
- Strap cuts wire rope to 1/4" diameter
 Maximum bardness of material to be cut:
- Brinell 455/Rockwell C48
- Lockplate keeps jaws from loosening
 Toggle joints turn 50 lbs. hand pressure
- Toggle joints turn 50 lbs. nand pressure to 4000 lbs. cutting pressure
 Screw-type adjustment realigns edges
- Screw-type adjustment realigns edges

Shear Type Cable Cutters

- Notched, shear-cut blades hold and lock cable in cutting position
- Cuts steel cable, coarse- or fine-stranded cable, or wire rope with minimal distortion
- Toggle joints turn 50 lbs. hand pressure to 4000 lbs. cutting pressure
- Screw-type adjustment realigns edges

							H.K. PORTER							
Model	Mfg.	Wt.		erall Igth	Cutting Capaci Rope Steel Cable					ble	Price	Replacement Cutter Model Mfg.		rhead Price
No.	No.	lbs.	in.	mm	in.	mm	in.	mm	in.	mm	/Each	No.	No.	/Each
TBG122	1490MTN	2.75	14	356	1/4	6	1/4	6	1/4	6		TBG111	1413TN	
TBF972	0190MTN	5	24	610	3/8	10	3/8	10	3/8	10		YC555	0113TN	
TBG047	0390MTN	12	36	914	5/8	16	5/8	16	5/8	16		TBG026	0313TN	
_					r									

Maximum

Capacity

in. mn

5/8 16

Cutting Capacity

Rockwell C48

in. mn

5/16 8

Rockwell C31

mm

11

in

7/16

Overall

Length

610

in. mr

24

Model

TBF967

Model

WK859

No.

Mfg.

0590RBJN

No

Wt.

lbs.

31

Length

mm

1320

in.

52

No.

Mfg.

0190MCS

No.

Wt

lbs

5.5

Rebar Cutters & Benders

- Rugged contractor's tool
- Shear-cut blades
 Mounts easily on
- most flat surfaces to enhance leverage and increase safety

Contact us now to receive our latest flyers

