

### **Economy Precision Scales**

- Maximum efficiency at minimal cost
- Top loading scales have a removable stainless steel platform making them easy to keep clean
- · Speed and precision at a low price
- · Ideal for small lab and educational environments

#### **FEATURES:**

- · External calibration, brushed stainless steel platter and adapter
- · Weights in g, oz., lbs., dwt, oz. t., cnt
- Counting features
- Operating temperature: 10°C to 35°C
- Dimensions: 7" W x 9 3/4" D x 2 1/2" H
- 1-year warranty






#### **NOT LEGAL FOR TRADE**

| Model No. | Mfg. No. | Capacity | Graduation | Platter Dimension | Price/Each |
|-----------|----------|----------|------------|-------------------|------------|
| PE130     | KLE-200  | 200 g    | 0.1 g      | 4.6" diameter     |            |
| PE131     | KLE-2000 | 2000 g   | 1 g        | 5" x 6.5"         |            |

### **Precision Scales**

- Fast microprocessing speed and digital filtration are the key to peak performance and stability
- · Single direction RS-232 allows you to connect to peripheral devices
- · Leveling bubble is included and all four feet are adjustable
- Features external calibration
- · Brushed stainless steel platter and adapter
- Weights in g, oz., lbs., dwt, oz. t., cnt and KHA 0.01 g also weights in CT
- Counting features
- Operating temperature: 10°C to 35°C
- 1-year warranty





#### **NOT LEGAL FOR TRADE**

| Model | Mfg.      |          |            | Platter Dimensions |   |      |     | Price |
|-------|-----------|----------|------------|--------------------|---|------|-----|-------|
| No.   | No.       | Capacity | Graduation | W"                 | х | D"   |     | /Each |
| IA780 | KHA-203R  | 200 g    | 0.001 g    | 4.75               | Х | 4.75 | No. |       |
| PE136 | KHA-1000R | 1000 g   | 0.01 g     | 4.75               | х | 4.75 |     |       |
| PE137 | KHA-1201R | 1200 g   | 0.1 g      | 6.94               | х | 6.94 |     |       |
| IA781 | KHA-5001R | 5000 g   | 0.1 g      | 6.94               | Х | 6.94 |     |       |



# Pesola® Micro Spring Scales

- Rotatable bow allows for ideal position of scale reading
- Screw for tare and for adjusting the zero position (range of tare = 20%)
- Innovative adjustment and suspension of spring
- Precise graduation, high resolution, abrasion-resistant and anodized colour
- Eye-clip with lower suspension rotates by 360°
- Eye-clip allows easy interchange of lower suspension with other accessories
- Vertical measuring position



| Mfg.<br>No. | Capacity | Graduation | Price<br>/Each |
|-------------|----------|------------|----------------|
| 20010       | 10 g     | 0.1 g      | •              |
| 20030       | 30 g     | 0.25 g     |                |
| 20060       | 60 g     | 0.5 g      |                |
| 20100       | 100 g    | 1.0 g      |                |

# Pesola® Medio Spring Scales

- Rotatable bow allows for ideal position of scale reading
- Screw for tare and for adjusting the zero position (range of tare = 20%)
- Innovative adjustment and suspension of spring
- Precise graduation, high resolution, abrasion-resistant and anodized colour
- Integrated recoil absorption (important for tensile tests with drag pointer 4.012 (IB721))
- Clear marker reading line on level of graduation
- Eye-clip allows easy interchange of lower suspension with other accessories

40300

40600

41000

41002

43000

42500/A

| Graduation | ¥.    | Price<br>/Each |
|------------|-------|----------------|
|            | _[6]_ | / Lacii        |
| 2 g        |       |                |
| 5 g        |       |                |
| 10 g       |       |                |
| 10 g       |       |                |
| 20 g       |       |                |
| 30 g       |       |                |

IB698

**IB699** 

**IB700** 

IB701

IB702\*

IB703\*

### Pesola® Macro Spring Scales

- · Rotatable bow allows for ideal position of scale reading
- Screw for tare and for adjusting the zero position (range of tare = 20%)
- Innovative adjustment and suspension of spring
- Precise graduation, high resolution, brasion-resistant and anodized colour
- Integrated recoil absorption for tensile tests with drag pointer (drag pointer supplied)
- · Clear marker reading line on level of graduation
- Swivel hook, rotatable and replaceable by different accessories



| Model | Mfg.  |                |              | Price |
|-------|-------|----------------|--------------|-------|
| No.   | No.   | Capacity       | Graduation   | /Each |
| IB705 | 80005 | 5 kg           | 50 g         |       |
| IB707 | 80015 | 10 lbs./5 kg   | 50 g/2 oz.   |       |
| IB706 | 80010 | 10 kg          | 100 g        |       |
| IB712 | 80210 | 20 lbs./10 kg  | 100 g/4 oz.  |       |
| IB708 | 80020 | 20 kg          | 200 g        |       |
| IB713 | 80420 | 40 lbs./20 kg  | 200 g/8 oz.  |       |
| IB709 | 80035 | 35 kg          | 500 g        |       |
| IB710 | 80050 | 50 kg          | 500 g        |       |
| IB711 | 80150 | 100 lbs./50 kg | 500 g/1 lbs. |       |

Capacity

300 g

600 g

1000 g

1000 g

2500 g

3000 g

IB694

**IB695** 

IB696

**IB697** 

<sup>\*</sup> Supplied with J hook