

Aluminum Service Jack & Stand Pack

- Pack includes 1 service jack and 2 jack stands
- Ideal for ground-hugging high-performance cars
- Jack stand features 6 holding positions to accommodate vehicles with low or high heights
- Made out of aircraft-grade aluminum for easy transport
- Service jack can go underneath vehicles as low as 3.4" by removing the saddle
- Service jack features quick-lift system where vehicles get in the air with only 5 pumps
- Jack stand has a minimum height of 9.5" and a maximum height of 15.16"
- Jack stands features a flat round base to prevent damages to surfaces
- Service jack features mounted handles on either side
- Lifting Capacity: 2 Ton(s) Lowered Height: 3-1/4"
- Raised Height: 18-1/2" Operation Type: Manual Hydraulic
- Service Jack Weight: 41 lbs. Wheel Diameter: 2.5"
- Caster Diameter: 1.75" Handle Length: 47.625'
- Service Jack Saddle Diameter: 4.5
- Jack Stand Saddle Size: 2.17"W X 1.97"D
- Jack Stand Base Diameter: 7"
- Jack Stand Weight: 4.7 lbs.
- Service Jack Meets: ASME PASE-2014



Model	Mfg		Price
No.	No.	Description	/Each
LW020	1533A	Jack & Stand	
LW019	1582A	Stand	
FLU021	LDJA2	Jack	



Aluminum Service Jack & Stand Pack

- Service Jack is ideal for ground-hugging high-performance cars
- Jack stand features 6 holding positions to accommodate vehicles with low or high heights
- All items are made out of aircraft-grade aluminum for easy transport
- Service jack can go underneath vehicles as low as 3.6" by removing the saddle
- Service jack features guick-lift system where vehicles get in the air with only 5 pumps
- Jack stand has a minimum height of 9.5" and a maximum height of 15.16"
- Jack stands features a flat round base to prevent damages to surfaces
- Service jack features mounted handles on either side
- Lifting Capacity: 3 Ton(s) Lowered Height: 3-5/8"
- Raised Height: 19-3/16" Operation Type: Manual Hydraulic
- Handle Length: 47.6" Service Jack Saddle Diameter: 4.6" Wheel Diameter: 2.6" Caster Diameter: 2"
- Service Jack Weight: 55 lbs.
- Jack Stand Saddle Size: 2.2"W X 2"D
- Jack Stand Base Diameter: 7.1" Jack Stand Weight: 4.74 lbs.
- Service Jack Meets: ASME PASE-2014



Model No.	Mfg No.	Description	Price /Each
LW021	1533A	Jack & Stand	
LW022	1532A	Jack	





Stinger Series Service Jack & Stand Pack

- Pack includes 1 service jack and 2 jack stands
- Service jack features reinforced construction for better stability
- Service jack features safety overload system that prevents use beyond its rated capacity
- Jack stand features 11 holding heights to accommodate various vehicles with low or high heights
- Jack stand features welded foot pads that prevent item from sinking into soft ground or asphalt
- Compact design makes items easy to manipulate and handle
- Lifting Capacity: 3 Ton(s)
- Lowered Height: 5-3/4"
- Raised Height: 18-1/2"
- Operation Type: Manual Hydraulic
- Saddle Diameter: 4"
- Overall Reach: 21"
- Frame Height: 6-1/2"
- Handle Length: 39-1/2"
- Floor space: 13-1/2"W X 24-1/2"D
- Jack Stand Lock Type: Locking Handle/Ratchet
- Jack Stand Height Range: 12" to 17-11/16"
- Jack Stand Base: 8-1/4"W x 7-1/2"D
- Jack Stand Weight: 7.25 lbs.



Model No.	Mfg No.	Description	Price /Each

