



Electrical Tape

aurora tools

- Vinyl plastic
- Excellent recovery, molds snugly to any surface
- Ideal for electrical splicing and insulation; protection against solvents and corrosion
- For use between -7°C and 80°C
- Thickness: 7 mils • CSA approved



Model No.	Colour	Dimensions	Price /Each	Qty	Qty Price /Each
XE890	Black	3/4" x 60' (19 mm x 18 m)			
XH383	Red	3/4" x 60' (19 mm x 18 m)			
XH384	Green	3/4" x 60' (19 mm x 18 m)			

Model No.	Colour	Dimensions	Price /Each	Qty	Qty Price /Each
XH385	Blue	3/4" x 60' (19 mm x 18 m)			
XH386	White	3/4" x 60' (19 mm x 18 m)			
XH387	Yellow	3/4" x 60' (19 mm x 18 m)			

Colourflex™ Tape

- General purpose colour coding vinyl tape
- Thickness: 7 mils



Priced per Roll

Model No.	Colour	Dimensions	Roll /Case	Price /Each	Qty	Qty Price /Each
XC316	Blue	3/4" x 60'	100			
XC317	Green	3/4" x 60'	100			
XC318	Red	3/4" x 60'	100			
XC319	White	3/4" x 60'	100			
XC320	Yellow	3/4" x 60'	100			
XC321	Orange	3/4" x 60'	100			

Temflex™ Electrical Tape

- General purpose, flexible vinyl tape designed for indoor or short term use and bundling
- Temperature rating: 176°F/80°C
- Colour: Black
- Thickness: 7 mil
- UL and CSA approved



Priced per Roll

Model No.	Dimensions	Roll /Case	Price /Each	Qty	Qty Price /Each
PC695	3/4" x 60' (19 mm x 18.3 m)	100			

Scotch® Super 88 Vinyl Tape

- All weather, premium grade vinyl tape for primary insulation up to 600 V or protective jacketing for low/medium voltage cable splices
- Aggressive adhesive and elastic backing ensures easy conformation to irregular surfaces for moisture tight electrical and mechanical protection
- Will perform in a continuous temperature environment up to 220°F (105°C)
- Conformable for cold weather applications: 0°F (-18°C)
- Thickness: 7 mil
- Colour: Black
- UL and CSA approved



Priced per Roll

Model No.	Dimensions	Roll /Case	Price /Each	Qty	Qty Price /Each
PC694	3/4" x 66' (19 mm x 20.1 m)	100			

Scotch® 130C Linerless Rubber Splicing Tape

- Highly conformable, linerless self-bonding ethylene propylene rubber (EPR) tape for insulating all solid dielectric cables up to 69 kV
- Excellent thermal dissipation of splice heat
- Meets industry specifications, excellent physical and electrical properties
- Immediate moisture sealing and void-free buildups
- Rated up to 194°F (90°C) continuous operation and up to 266°F (130°C) short-term overload service
- Having no liner makes jobs easier and saves time
- Thickness: 30 mils



Priced per Roll

Model No.	Dimensions	Rolls/Case	Price/Each	Qty	Qty Price/Each
AF284	3/4" x 30'	24			
XC323	1" x 30'	24			
XH307	1-1/2" x 30'	12			

Scotch® Super 33+ Vinyl Tape

- All weather, premium grade vinyl tape for primary insulation up to 600 V or protective jacketing for low/medium voltage cable splices and repairs
- Aggressive adhesive and elastic backing ensures easy conformation to irregular surfaces for moisture tight electrical and mechanical protection
- Will perform in a continuous temperature environment up to 220°F (105°C)
- Conformable for cold weather applications: 0°F (-18°C)
- Thickness: 7 mil
- Colour: Black
- UL and CSA approved




Priced per Roll

Model No.	Dimensions	Roll /Case	Price /Each	Qty	Qty Price /Each
PC693	3/4" x 66' (19 mm x 20.1 m)	100			

Scotch® 35 Colour Coding Vinyl Tape

- Premium grade vinyl electrical colour-coding tape for phase and job identification and safety
- Heavy-duty, premium grade
- Temperature rating: 220°F/105°C
- Thickness: 7 mil
- UL and CSA approved



Priced per Roll

Model No.	Colour	Dimensions	Rolls /Case	Price /Each	Qty	Qty Price /Each
PC696	Blue	1/2" x 20'	100			
PC720	Green	1/2" x 20'	100			
PC721	Red	1/2" x 20'	100			
PC722	White	1/2" x 20'	100			
PC723	Yellow	1/2" x 20'	100			
XC309	Orange	1/2" x 20'	100			
PE118	Blue	3/4" x 66'	100			
PE120	Green	3/4" x 66'	100			
XC312	Red	3/4" x 66'	100			
PE119	White	3/4" x 66'	100			
XC314	Yellow	3/4" x 66'	100			
XC315	Orange	3/4" x 66'	100			

Scotch® 27 Glass Cloth Electrical Tape

- Ideal for electrical maintenance applications
- Woven glass cloth tape with a rubber thermosetting pressure-sensitive adhesive
- Edge-tear resistant, conformable, abrasion resistant
- For use as a coil cover, anchor, banding and core, layer and crossover insulation, and for heat-stable insulation for furnace and oven controls, motor leads, and switches
- Thickness: 7 mils
- UL recognized 130°C/266°F



Priced per Roll

Model No.	Dimensions	Rolls/Case	Price/Each	Qty	Qty Price/Each
XH289	1/2" x 66' (12 mm x 20.1 m)	10			
XC322	3/4" x 66' (19 mm x 20.1 m)	50			