

#### 950-W Portable Generators

- Compact and portable gasoline generator
- Powerful 2 HP, 2 stroke air cooled motor
- Brushless alternator and electric ignition
- Outlet: 120 V/6.7 A, AC output
- Outlet: 12 V/5.3 A, DC output
- Easy start manual recoil starter
- AC and DC circuit breakers and reset buttons for safe operation
- Rubber feet reduce vibration and prevent crawling
- Comes with DC cables and spark plug socket
- CSA and EPA approved

Model No. TGZ378



#### 1800-W Gas Generator

- Powerful 3 HP, 4 stroke air cooled OHV engine
- Low oil shut-off with indicator light protects the engine
- Easy start recoil starter
- AC and DC circuit breakers for safe operation
- Comes with DC cables and spark plug socket
- CSA and EPA approved
- Oil Capacity: 0.5 L
- Voltage Output: 120 V

Model No. XI539



## 5100-W Generator with Wheel Kit

- Powerful 8 HP, 4 stroke air cooled OHV engine
- AVR system and electronic ignition
- Easy start recoil starter
- AC double throw circuit breaker and resets for safe operation
- Includes: (2) 8" wheels, (1) Pivot handle, (1) Spark plug socket
- Fuel: Unleaded Gasoline
- Oil Capacity: 0.6 L
- Noise level: 75 dB
- Voltage Output: 120 V, 240 V

Model No. XI497



### 6500-W Electric Start Gas **Generator with Wheel Kit**

- Powerful 10 HP, 4 stroke air cooled OHV engine
- AVR system and electronic ignition
- Low oil shut-off with indicator light protects the engine
- Keyed electric start and easy start recoil starter
- AC double throw circuit breaker and resets for safe operation
- Neutral bonded to frame
- Features two duplex outlets (120V) and one twist lock outlet (120V & 240V)
- CSA and EPA approved
- · Includes: 8" Wheels, Pivot handle, 12 V Battery, Spark plug socket
- Oil Capacity: 0.7 L

Model No. XI537



#### 8500-W Gasoline Generators

- Powerful 15 HP, 4 stroke air cooled OHV engine
- AVR system and electronic ignition
- Low oil shut-off with indicator light protects the engine
- Two duplex outlets: 120 V/20 amp AC
- Two twist lock outlets: 120 V/30 Amp and 120 V/240 V/30 Amp AC
- Keyed electric start and easy start recoil starter
- AC double throw circuit breaker and resets for safe operation
- Wheel kit includes 10" wheels and pivot handles
- Neutral bonded to frame
- AC Outputs: 52 Amps / 26 Amps No load speed: 3600 RPM
- Displacement: 420 cc
- Fuel: Unleaded gasoline
- Oil capacity: 1.1 L Noise level: 73 dB
- **Assembled Dimensions:** 31.5" L x 28.5" W x 25.375" H
- CSA & EPA approved

Model No. NJ360



# 12000-W Electric Start Gas **Generator with Wheel Kit**

- AVR system and electronic ignition
- Low oil shut-off with indicator light protects the engine
- Keyed electric start and easy start recoil starter
- AC double throw circuit breaker and resets for safe operation
- Features an ammeter/voltmeter and frequency/time digital meter
- Neutral bonded to frame
- Features two 120V/20 Amp duplex outlets, one 120 V/30 Amp twist lock outlet, and one 120V/240V/50 Amp outlet
- Includes: 10" Wheels, Pivot handle, 12V Battery, Spark plug socket
- Oil Capacity: 1.1 L

Model No. XI538



Model	Mfg.	AC	DC		Max Power	Fuel Tank	Run Time	Wt.	Price
No.	No.	Output	Output	Amps	(HP)	Capacity (L)	(hrs.)	lbs.	/Each
TGZ378	KCG-951G	800 W (rated), 950 W (max.)	12 V/5.3 A	6.7 A	2	4.2	4-5	40	
XI539	KCG-1501GX	1400 W (rated), 1800 W (max.)	-	-	3	7	9	56	
XI497	KCG-5100G	4000 W (rated), 5100 W (max.)	-	-	8	15	7-8	107	
XI537	KCG-6502GE	5000 W (rated), 6500 W (max.)	-	-	10	20	7-8	135	
NJ360	KCG-8500GE	6250 W (rated), 8500 W (max.)	-	-	15	25	7	195	
XI538	KCG-12000GE	9000 W (rated), 12 000 W (max.)	-	-	18	31	6	250	



