



## Beacon LED Four-Light Tower

- Whisper-quiet operation
- Runs on multiple power sources, including external power, user supplied suitcase generator, or fuel tank
- Tower can be lifted into the back of a pick-up truck, and two towers can fit in the truck bed for easy transportation
- The steel frame chassis and mast are robust enough to withstand any job site condition
- Ability to daisy-chain multiple towers and tools
- 2 towers can run on a 15A circuit
- Comes with hose and fuel cap that will fit most popular suitcase generator models
- Power Type: Diesel, Electric
- Running Watts: 800 Watts
- Total Lumens: 120,000
- Mast Height: 17'
- Mast Type: Vertical
- Voltage: 90 - 277 V
- Environmental Rating: IP65
- Housing Material: Aluminum
- Lamp Life: 50000 hrs.
- Weight: 380 lbs.
- Fuel Tank Capacity: 23 L (6 US gal.)



Model No.	Mfg. No.	Price /Each
XI327	LE980LEDV-T4	P.O.A.

## MLT4060 LED Light Towers

- Built and designed for the most extreme environments
- Adjustable and fully-rotational mast
- Robust 14-gauge steel enclosure
- Broad-based design for stable transport in rough terrain
- Withstands winds up to 105 kph
- Equipped with a Mitsubishi® L3E 3-cylinder engine
- Automatic low oil/high temperature shutdown system
- CSA approved
- 104 gal. fuel capacity
- Power Type: Diesel
- Running Watts: 6000 Watts
- Total Lumens: 88,000
- Mast Height: 23'
- Mast Type: Vertical
- Standby Power Rating: 12.2 hp @ 1800 rpm
- Prime Power Rating: 10.5 hp @ 1800 rpm
- Full Load Fuel Consumption: 0.549 gph
- Lights Only Fuel Consumption: 0.195 gph
- Maximum Run Time Lights Only: 533 hours
- Voltage: 120/240 VAC
- Amperage: 50/25 Amps



Model No.	Price /Each
XG901	P.O.A.

## MLT3060 Light Towers

- Built and designed for the most extreme environments
- Adjustable and fully-rotational mast
- Robust 14-gauge steel enclosure
- Withstands winds up to 105 kph
- Automatic low oil/high temperature shutdown system
- CSA approved
- 33.6 gal. fuel capacity
- Power Type: Diesel
- Running Watts: 6000 Watts
- Total Lumens: 462,000
- Voltage: 120/240 VAC
- Amperage: 50/25 Amps



Model No.	Mast Height'	Mast Type	Standby Power Rating	Prime Power Rating	Full Load Fuel Consumption	Lights only Fuel Consumption	Max. Run Time Lights Only (hrs)	Equipped With	Price /Each
XG893	30	Horizontal	15.4 hp @ 1800 rpm	13.5 hp @ 1800 rpm	0.50 gph	0.25 gph	134	Kubota® D1105-E3BG 3 cylinder engine	P.O.A.
XG894	25	Vertical	15.4 hp @ 1800 rpm	13.5 hp @ 1800 rpm	0.50 gph	0.25 gph	134	Kubota® D1105-E3BG 3 cylinder engine	P.O.A.
XG895	30	Horizontal	12.2 hp @ 1800 rpm	10.5 hp @ 1800 rpm	0.47 gph	0.24 gph	140	Mitsubishi® L3E-W461ML 3 cylinder engine	P.O.A.
XG896	25	Vertical	12.2 hp @ 1800 rpm	10.5 hp @ 1800 rpm	0.47 gph	0.24 gph	140	Mitsubishi® L3E-W461ML 3 cylinder engine	P.O.A.

## MLT4060 Light Towers

- Built and designed for the most extreme environments
- Adjustable and fully-rotational mast
- Robust 14-gauge steel enclosure
- Broad-based design for stable transport in rough terrain
- Withstands winds up to 105 kph
- Automatic low oil/high temperature shutdown system
- CSA approved
- 56.4 gal. fuel capacity
- Power Type: Diesel
- Running Watts: 6000 Watts
- Total Lumens: 462,000
- Voltage: 120/240 VAC
- Amperage: 50/25 Amps



Model No.	Mast Height'	Mast Type	Standby Power Rating	Prime Power Rating	Full Load Fuel Consumption	Lights only Fuel Consumption	Max. Run Time Lights Only (hrs)	Equipped With	Price /Each
XG897	30	Horizontal	15.4 hp @ 1800 rpm	13.5 hp @ 1800 rpm	0.50 gph	0.25 gph	225	Kubota® D1105-E3BG 3 cylinder engine	P.O.A.
XG898	25	Vertical	15.4 hp @ 1800 rpm	13.5 hp @ 1800 rpm	0.50 gph	0.25 gph	225	Kubota® D1105-E3BG 3 cylinder engine	P.O.A.
XG899	30	Horizontal	12.2 hp @ 1800 rpm	10.5 hp @ 1800 rpm	0.47 gph	0.24 gph	235	Mitsubishi® L3E-W461ML 3 cylinder engine	P.O.A.
XG900	25	Vertical	12.2 hp @ 1800 rpm	10.5 hp @ 1800 rpm	0.47 gph	0.24 gph	235	Mitsubishi® L3E-W461ML 3 cylinder engine	P.O.A.