



## Blowers

- X-Torq® engine design reduces harmful exhaust emissions by up to 60% and increases fuel efficiency by up to 20%
- Air Purge removes air from carburetor and fuel system for easy starting
- Offset handle makes the blow forces easier to control by preventing the arm from being pulled downwards



SPECIFICATIONS	525Bx	560BTs	570BTs	580BTs
Displacements (CC)	25.4	65	65	75.6
Engine Power (HP)	1.14	4	4	4.3
Air Speed (CFM/MPH)	459/157	632/236	770/236	936/212
Harness	Integrated	Integrated	Integrated	Integrated
Nozzle Type	Round	Round	Round	Round
Vacuum Kit	-	-	-	-
Weight (lbs./kg)	9.5/4.3	23.4/10.6	24.5/11.1	26.3/11.9
Model No.	NL865	NL921	NM889	NN313
Mfg. No.	967 28 42-02	966 63 11-02	966 62 94-02	967 85 13-01
Price/Each	\$	\$	\$	\$

SPECIFICATIONS	125B	125BVx	130BT	350BT	320LiB *	436LiB **
Displacements (CC)	28	28	29.5	50	-	-
Engine Power (HP)	1.1	1.1	1.3	2.1	-	-
Air Speed (CFM/MPH)	425/170	425/170	360/145	494/180	412/103	388/105
Harness	-	Single Harness	Integrated	Integrated	-	-
Nozzle Type	Round + Flat	Round + Flat	Round	Round	Round	Round
Vacuum Kit	-	Yes	-	-	-	-
Weight (lbs./kg)	9.4/4.3	9.6/4.4	14.8/6.7	22.5/10.2	5.29/2.4	5.29/2.4
Model No.	NL855	NL873	TYX949	NL906	NL890	NM890
Mfg. No.	952 71 19-25	952 71 19-02	965 10 22-08	965 87 75-02	967 09 42-02	967 68 02-02
Price/Each	\$	\$	\$	\$	\$	\$

\* Battery and charger included \*\* Unit only, battery and charger sold separately

## Power Cutters

- Husqvarna power cutters are robust, reliable and powerful machines
- Compact and powerful machine with superior power-to-weight ratio
- Dust-sealed starter device and the durable starter cord, assures the saw will be ready for work whenever you want



SPECIFICATIONS	K 760 - 12"	K 760 - 14"	K 970 - 14"	K 970 III - 14" Rescue Saw	K 1270 - 16"
Displacements (CC)	73.5	73.5	94	93.6	118.8
Engine Power (HP)	4.9	5	6.5	6.5	7.9
Max Cutting Depth (in.)	5	4.92	5	5	6
Vibration Front (m/s <sup>2</sup> )	2.4	2.4	3.7	3.8	6.9
Vibration Rear (m/s <sup>2</sup> )	2.4	2.4	4.5	4.2	6.3
Active Air Filtration™	Yes	Yes	Yes	Yes	Yes
X-Torq®	No	Yes	Yes	No	Yes
Sound Level (dB(a))	115	115	116	115	117
Weight excl. acc. (lbs. / kg)	21.2/9.6	22.3/10.1	24.2/11.0	24.2/11.0	31.7/14.4
Model No.	NM891	NN014	NM572	NM892	NM893
Mfg. No.	967 18 10-01	967 68 21 01	967 34 80-01	967 63 56-01	967 05 42-01
Price/Each	\$	\$	\$	\$	\$

## Cutting Blades

Model No.	Mfg. No.	Specifications	Diameter"	Thickness"	Arbor Size	Price/Each
<b>ABRASIVE BLADES</b>						
NM895	542 75 15-04	General Concrete, Asphalt and Brick	14	-	1"	
NM896	542 75 15-10	Steel	14	-	1"	
NM897	542 75 15-16	Ductile Iron/Aluminum	14	-	1"	
NM898	542 75 15-11	Steel	14	-	20 mm	
NM899	542 75 15-12	Steel	16	-	1"	
<b>PREMIUM BLADES</b>						
NM900	542 77 45-41	HI-5 Premium Diamond Blade	14	0.125	1"- 20 mm Knockout	
NM901	542 77 65-04	HI-8 Premium Diamond Blade	14	0.125	1"- 20 mm Knockout	
<b>CHOICE BLADES</b>						
NL869	542 77 87-35	EH-5 Choice Diamond Blade	14	0.125	1"- 20 mm Knockout	
NM902	589 71 93-01	EH-5 Choice Diamond Blade	16	0.140	1"- 20 mm Knockout	
NM903	542 77 55-98	EH-8 Choice Diamond Blade	16	0.140	1"- 20 mm Knockout	