



## Gas-Powered Pressure Washers

### MEDIUM-DUTY PROFESSIONAL

- 6.5 HP Honda® GX motor
- Integrated detergent feed system with adjustable unloader
- Industrial pump with ceramic plungers and thermal protection
- Four quick connect nozzles with lance

Cleaning Units	7500
Pump Pressure	2500 PSI
Flow Rate	3.0 GPM
Hose Length	30'
Gun/Lance	115 cm
Low Oil Sensor	Yes
Thermal Protection	Yes
Dimensions	23.5" x 32.5" x 27"
Shipping Weight	98 lbs.

Model No. TEB610  
Mfg. No. KC3250GPC  
Price/Each \$

### HEAVY-DUTY PROFESSIONAL

- 13 HP Honda® GX motor
- Integrated detergent feed system with adjustable unloader
- Industrial pump with ceramic plungers and thermal protection
- Four quick connect nozzles with lance

Cleaning Units	13 300
Pump Pressure	3500 PSI
Flow Rate	3.8 GPM
Hose Length	50'
Gun/Lance	145 cm
Low Oil Sensor	Yes
Thermal Protection	Yes
Dimensions	23.5" x 32.5" x 27"
Shipping Weight	150 lbs.


Model No. TEB611  
Mfg. No. KC4350GPC  
Price/Each \$



## Cold Water Pressure Washers

- Kodiak 15HP OHV Engine
- Engine oil alert
- Interpump triplex plunger pump
- Built in low pressure injector chemical
- Built in unloader
- PA RL37 Gun
- Pump thermal protection
- 4 colour coded quick connect nozzle
- Powder coated convertible cart
- Assembled in Canada
- Never go flat 10" wheels
- Pump Pressure: 4000 PSI
- Flow Rate: 4.0 GPM
- Engine Power: 15 HP
- Hose Length: 50'
- Cleaning Units: 16 000
- Operating Type: Gasoline
- Weight: 155 lbs.

Model No. NJ372  
Mfg. No. RT40002  
Price/Each \$



## Accessories

### QUICK CONNECT NOZZLES

- Hardened stainless steel orifice in a stainless steel housing
- Nozzles colour coded based on orifice size
- Available in 0° (red), 15° (yellow), 25° (green), and 40° (white) spray angle



Model No.	Mfg. No.	Spray Angle°	1000 PSI	2000 PSI	3000 PSI	Flow rate GPM @	
						4000 PSI	5000 PSI
						Price /Each	
NJ055	PWQC004	0	2	2.83	3.46	4.02	4.49
NJ056	PWQC1504	15	2	2.83	3.46	4.02	4.49
NJ057	PWQC2504	25	2	2.83	3.46	4.02	4.49
NJ058	PWQC4004	40	2	2.83	3.46	4.02	4.49

### ZINC-PLATED LANCES

- 3000 PSI rated pressure
- 1/4" inlet
- 1/4" outlet



Model No.	Mfg. No.	Description	Price/Each
NJ049	L1	36" Round Molded Strip	
NJ050	L2	48" Round Molded Strip	

### BLACK HOSES

- 250°F max. temperature
- 3/8" MPT solid end
- 3/8" MPT swivel end
- Molded vinyl bend restrictors
- Steel wire braid for 4:1 burst factor
- Quick disconnect plugs and sockets are sold separately



Model No.	Mfg. No.	Hose Length'	Pressure (PSI)	Price /Each
NJ039	HW25	25	4000	
NB896	HW30	30	4000	
NB897	HW50	50	4000	
NJ042	HW100	100	4000	
NJ043	HW150	150	4000	

### RL37 SPRAY GUNS

- 4500 PSI max. pressure
- 10.5 GPM max. flow
- 320°F max. temperature
- 3/8" NPT-F inlet or QC depending upon model
- 1/4" NPT-F outlet or QC depending upon model
- Weight: 20.0 oz.



Model No. NJ059  
Mfg. No. RL37  
Price/Each \$

### QUICK DISCONNECT PLUGS & SOCKETS

- Standard O-rings
- EPR with Teflon® coating



Model No.	Mfg. No.	Description	Price/Each
NJ051	QC7195	Plated steel 3/8" F plug	
NJ052	QC7196	Plated steel 3/8" M plug	
NJ053	QC7214	Brass 1/4" F socket	
NJ054	QC7210	Brass 1/4" M socket	

### BLUE NON-MARKING HOSES

- 250°F max. temperature
- 3/8" MPT solid end
- 3/8" MPT swivel end
- Steel wire braid
- Quick disconnect plugs and sockets are sold separately



Model No.	Mfg. No.	Hose Length'	Pressure (PSI)	Price /Each
NJ044	HW50BLUE	50	4000	
NJ045	HW75BLUE	75	4000	
NJ046	HW100BLUE	100	4000	