

## **Multiple Surface Bonding Structural Adhesives**

- Bonds a wide variety of materials, such as metal, ceramics and plastics
- Perfect for the following industries: machining & tooling, recreational vehicles, furniture making/repair, structural building components, appliances

# 330™ Depend® No-Mix Adhesive

- A high viscosity adhesive for a wide range of materials including metal, wood, ferrite, ceramic and plastic
- For rough or porous surfaces
- Ideal for gap distances up to 0.030"
- Fixtures in 5 minutes, full in 24 hrs.
- Provides a shear strength of 3300 PSI
- · Withstands temperatures to 250°F
- Recommended 7387 primer
- · Colour: Amber



#### LOCTITE

Model	Mfg.	e:	Price		ty Price
No.	No.	Size	/Each	Qty	/Each
AB357	1690727	25 ml Kit*			
AC329	1691005	250 ml Kit**		-	-

\*Contains 25 ml syringe of Depend 330 and 25 g. aerosol can activator, 7387.

\*\* Contains 250 ml tube of Depend 330 and 4.5 fl. oz. aerosol can activator, 7387.

## Hysol® E-00CL Fast Setting Epoxy

- Ideal for general purpose bonding, potting, or encapsulating
- Works on a variety of plastic, metal, glass, rubber, wood, and ceramic substrates
- Well suited for applications that require a clear bondline
- Flowable and low odour
- 3-5 minutes worklife
- 1:1 mix ratio (resin:hardener)
- 2000-4000 PSI overlap shear strength
- Colour: Clear



LOCITIE
---------

Model No.	Mfg. No.	Size	Price /Each	Q Qty	ty Price/Each
AC351 AF085	237095 237096	50 ml 200 ml			

## Hysol® E-30CL Epoxy

- Glass bonder, low viscosity, impact resistant
- 30 minutes worklife
- 2:1 mix ratio (resin:hardener)
- 2000-4000 PSI overlap shear strength
- · Colour: Ultra clear



#### LOCTITE.

Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AC350	237116	50 ml			
AF093	237117	200 ml			
Δ <b>F</b> 094	237118	500 ml		_	

### 312™ Acrylic Adhesives

- Ultra fast setting two-step acrylic
- No mixing required
- Should be used in conjunction with Loctite 736 to create a durable bond on close fitting parts
- · Colour: Amber



Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AF082	228191	10 ml Kit	1		
AF083	228173	50 ml Kit			

## Hysol® 1C General Purpose Epoxy

- Bonds, seals, and repairs a wide variety of materials
- · For metals, most plastics, and wood
- Gap filling for high temperatures
- · 20 minutes worklife
- · 2.5:1 mix ratio (resin:hardener)
- · 1750 PSI overlap shear strength
- Colour: White



#### LOCTITE.

Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AC359	1373425	4 oz. Kit			
AF087	1377344	1 gal. Kit		-	-
AF088	1377777	60-lb. Pail, Resin		-	-
AF089	1377780	40-lb. Pail, Hardener		-	-

## Hysol® E-60NC Potting Compound

- Bonding, potting and encapsulating electrical components which are sensitive to corrosion caused by traditional epoxies
- Use in electronic applications, for component attachmentto boards, housing assembly and potting
- Non-corrosive, low viscosity
- · 60 minutes worklife
- 1:1 mix ratio (resin:hardener)1000-3000 PSI overlap shear strength
- Colour: Black opaque

				941	
Model No.	Mfg. No.	Size	Price /Each	Qty	ty Price/ Each
AC354	237113	50 ml Dual Cartridge			
AF095	237114	200 ml Dual Cartridge			
AF096	237115	400 ml Dual Cartridge			
AF097	233988	5 gal. Pail, Resin		-	-
AF098	233990	5 gal Pail Hardener		_	_

## 331™ Structural Adhesive Ultra-Fast Ficture

- · Toughened, activator-cure acrylic
- · Acid-free, non-corrosive to sensitive parts
- Fixtures in 20 seconds and develops full strength in 30 minutes
- Excellent high temperature resistance
- Ideal for bonding close-fitting metals and magnets



### LOCTITE.

Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AD126	1057673	25-ml syringe			

## Hysol® E-20HP High Performance Epoxy

- Bond strengths to a wide variety of plastics and metals
- Ideal for general purpose industrial assemblies
- High strength, peel, shear and rubber toughened
- 20 minutes worklife
- 2:1 mix ratio (resin:hardener)
- 3000-5000 PSI overlap shear strength
- Colour: Off-white



#### LOCTITE.

Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AC348	237107	50 ml Dual Cartridge			
AF090	237108	200 ml Dual Cartridge			
AB926	237109	400 ml Dual Cartridge		-	-
AF091	233981	5 gal. Pail, Resin		-	-
AF092	233983	5 gal. Pail, Hardener		-	-

## H3000 Speed Bonder™ General Purpose

- A low viscosity adhesive
  Ideal for bonding
  plastics and composites
- Colour: Tan



#### LOCTITE

Model	odel Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AC343	398426	50 ml Cartridge			
AF084	398425	400 ml Cartridge			