



## Solo Gas Detectors

- Easy-to-service, single-gas detector
- Lightweight convenience
- High standards of sensor quality and reliability
- Compatible with IntelliDoX
- Bump testing (qualitative function check) of the sensors, is a recommended function and requires test gas cylinders and bump test accessories

### WIRELESS MODELS

- Provides real-time visibility into the status and safety of hazardous-area workers
- Connected Bluetooth low energy (BLE) capabilities
- Wireless feature allows access from any device with an internet connection to get remote visibility on worker safety and location

# Honeywell



HZ329

Yellow Model No.	Mfg. No.	Black Model No.	Mfg. No.	Hazard	Measuring Range	Price /Each
<b>STANDARD</b>						
HZ329	BWS-C-Y	HZ346	BWS-C-B	Cl <sub>2</sub>	0 ppm to 100 ppm	
HZ330	BWS-V-Y	HZ347	BWS-V-B	ClO <sub>2</sub>	0 ppm to 100 ppm	
HZ331	BWS-ML-Y	HZ348	BWS-ML-B	CO	0 ppm to 2000 ppm	
HZ332	BWS-M2-Y	HZ349	BWS-M2-B	CO	0 ppm to 2000 ppm	
HZ333	BWS-E-Y	HZ350	BWS-E-B	ETO	0 ppm to 50 ppm	
HZ334	BWS-R-Y	HZ351	BWS-R-B	H <sub>2</sub>	0 ppm to 1 ppm	
HZ335	BWS-HL-Y	HZ352	BWS-HL-B	H <sub>2</sub> S	0 ppm to 100 ppm	
HZ336	BWS-H2-Y	HZ353	BWS-H2-B	H <sub>2</sub> S ext range	0 ppm to 1000 ppm	
HZ337	BWS-Z-Y	HZ354	BWS-Z-B	HCN	0 ppm to 100 ppm	
HZ338	BWS-A-Y	HZ355	BWS-A-B	NH <sub>3</sub>	0 ppm to 200 ppm	
HZ339	BWS-A2-Y	HZ356	BWS-A2-B	NH <sub>3</sub> ext range	0 ppm to 500 ppm	
HZ340	BWS-N-Y	HZ357	BWS-N-B	Nitric Oxide	0 ppm to 250 ppm	
HZ341	BWS-D-Y	HZ358	BWS-D-B	NO <sub>2</sub>	0 ppm to 100 ppm	
HZ342	BWS-XL-Y	HZ359	BWS-XL-B	O <sub>2</sub>	0 v/v to 0.3 v/v	
HZ343	BWS-G-Y	HZ360	BWS-G-B	O <sub>2</sub>	0 ppm to 1 ppm	
HZ344	BWS-P-Y	HZ361	BWS-P-B	PH <sub>3</sub>	0 ppm to 5 ppm	
HZ345	BWS-S-Y	HZ362	BWS-S-B	SO <sub>2</sub>	0 ppm to 100 ppm	

### WIRELESS

HZ363	BWS1-C-Y	HZ380	BWS1-C-B	Cl <sub>2</sub>	0 ppm to 100 ppm	
HZ364	BWS1-V-Y	HZ381	BWS1-V-B	ClO <sub>2</sub>	0 ppm to 100 ppm	
HZ365	BWS1-ML-Y	HZ382	BWS1-ML-B	CO	0 ppm to 2000 ppm	
HZ366	BWS1-M2-Y	HZ383	BWS1-M2-B	CO	0 ppm to 2000 ppm	
HZ367	BWS1-E-Y	HZ384	BWS1-E-B	ETO	0 ppm to 50 ppm	
HZ368	BWS1-R-Y	HZ385	BWS1-R-B	H <sub>2</sub>	0 ppm to 1 ppm	
HZ369	BWS1-HL-Y	HZ386	BWS1-HL-B	H <sub>2</sub> S	0 ppm to 100 ppm	
HZ370	BWS1-H2-Y	HZ387	BWS1-H2-B	H <sub>2</sub> S ext range	0 ppm to 1000 ppm	
HZ371	BWS1-Z-Y	HZ388	BWS1-Z-B	HCN	0 ppm to 100 ppm	
HZ372	BWS1-A-Y	HZ389	BWS1-A-B	NH <sub>3</sub>	0 ppm to 200 ppm	
HZ373	BWS1-A2-Y	HZ390	BWS1-A2-B	NH <sub>3</sub> ext range	0 ppm to 500 ppm	
HZ374	BWS1-N-Y	HZ391	BWS1-N-B	Nitric Oxide	0 ppm to 250 ppm	
HZ375	BWS1-D-Y	HZ392	BWS1-D-B	NO <sub>2</sub>	0 ppm to 100 ppm	
HZ376	BWS1-XL-Y	HZ393	BWS1-XL-B	O <sub>2</sub>	0 v/v to 0.3 v/v	
HZ377	BWS1-G-Y	HZ394	BWS1-G-B	O <sub>2</sub>	0 ppm to 1 ppm	
HZ378	BWS1-P-Y	HZ395	BWS1-P-B	PH <sub>3</sub>	0 ppm to 5 ppm	
HZ379	BWS1-S-Y	HZ396	BWS1-S-B	SO <sub>2</sub>	0 ppm to 100 ppm	

## GasAlertMax XT II Multi-Gas Detectors - Five Unit Cradle Charger

- Gas Detector Series: GasAlertMax XT
- Parts: Charger

Model No. HX926  
Mfg. No. XT-C01-MC5  
Price/Each \$



# Honeywell

## IntelliDoX Docking Stations

- The IntelliDoX system is expandable to five docking modules helping you drive productivity, reliability and efficiency
- Provides a new level of customization for bump testing, configuration and record-keeping in a maintenance-free detector
- Configure alarm set points and change detector settings throughout the operation life of the BW Clip
- Quick and easy setup — great for turnarounds
- Each module has its own easy-to-read LCD screen and keypad for independent operation

HZ402



# Honeywell

Model No.	Mfg. No.	Compatible with	Price/Each
HZ187	DX-CLIP	BW Clip	
HZ286	DX-MCLP	BW MicroClip XL / MicroClip X3	
HZ402	DX-SOLO	BW Solo	
HZ404	DX-ULTRA	BW Ultra	

### ACCESSORIES

Model	Mfg. No	Description	Price/Each
HZ188*	DX-ENBL-NA	Enabler Kit	
HZ190	DX-MI-KEY	Multi-Inlet Key, For Solo only	

\* Enabler Kit includes power supply with region-specific AC power cord, ethernet cable, inlet (purge) filter assembly, 3 ft. / 1 m calibration gas tubing, 3 ft. / 1 m purge gas tubing, 15 ft. / 4.5 m exhaust tubing, quick connect fittings and IntelliDoX inlet end plate.

## MicroDock II Automated Instrument Docking Stations

- Fully automatic "hands-free" calibration, functional bump testing, record keeping and charging
- Automatically verifies performance of sensors, as well as audible and visual alarms
- Stores and updates calibration records in the MicroDock II, as well as in data logging instruments
- Quick and easy compliance – simple, automatically maintained accurate records
- Light weight and fully portable with optional wall mount
- Operates via 6-V line power or four C-cell batteries (batteries not included)
- Fully customizable
- Add self-contained docking modules to the system via simple, plug-in connections
- Multiple Microdock II systems can be connected via a LAN
- Includes BW Fleet Manager II software for easy data analysis
- Multi-language support in English, French, German, Spanish, and Portuguese
- One base station with one AC outlet supports up to ten modules to suit your application



MicroDock II shown with assorted docking modules

# Honeywell

Model No.	Mfg. No.	Docking Module Type	Price/Each
<b>BASE STATION WITH DOCKING MODULE &amp; CHARGING CABLE</b>			
HX917	DOCK2-2-1C1P-00-G	GasAlertMicroClip XT	
HX909	DOCK2-2-1C1N-00-G	GasAlertQuattro	
HX927	DOCK2-2-1C1M-00-G	GasAlertMax XT	
HX941	DOCK2-2-1C1K-00-G	GasAlertMicro 5	

<b>BASE STATION WITH DOCKING MODULE (NO CHARGING CABLE)</b>			
HX918	DOCK2-2-1P-00-G	GasAlertMicroClip XT	
HX910	DOCK2-2-1N-00-G	GasAlertQuattro	
HX928	DOCK2-2-1M-00-G	GasAlertMax XT	
HX942	DOCK2-2-1J-00-G	GasAlertMicro 5	

DOCKING MODULE ONLY			
HX920	DOCK2-0-1P-00-G	GasAlertMicroClip XT	
HX912	DOCK2-0-1N-00-G	GasAlertQuattro	
HX930	DOCK2-0-1M-00-G	GasAlertMax XT	
HX944	DOCK2-0-1J-00-G	GasAlertMicro 5	