EZ-Stop[™] Shock Absorbing Lanyards

the world; 66% smaller and 40% lighter than previous EZ-Stop[™] models

Features the lightest, smallest, and strongest shock absorber in

Vectran® is a multifilament high tenacity performance fibre spun

Shockwave[™] 2 Lanyards

- Tubular core style lanyards uniquely designed to
- expand and contract in reaction to a workers movements Stays out of your way when not in use, avoiding trips and snags

SEB869

Harness

Connection

Snap Hook

Snap Hook

Snap Hook

Pro™ Pack Shock Absorbing Lanyards

Anchorage

Connections

Snap Hook

Snap Hooks

Snap Hook

Anchorage

Connections

Snap Hook

Snap Hook

Gate Hook

Gate Hooks

Gate Hooks

Built in impact indicator provides visual evidence if the lanyard has been involved in a fall

No. of

Legs

One

Two

0ne

Pack-type shock absorber limits fall arrest forces to 900 lbs. for added safety Durable 1" polyester web construction Durable alloy steel, zinc-plated hardware Harness Connection: Snap Hook Certification(s): CSA Standard Z259.11

SEB872

PROTECTA

Fall Protection

Length'

6

6

NOMEX/KEVLAR ARC FLASH RATED LANYARDS

Length: 6

Fall Protection Model

No

SEB868

SEB869

SEP841

SE

Mode

SEB871

SEB872

SEB384

SEF153

SES801

No.

Mfg.

STANDARD LANYARDS

12443060

12424500

12446100

No.

Certification(s): CSA Standard Z259.11

from liquid crystal polymer that is five times stronger than steel Repel[™] webbing repels water to reduce the attraction of mold and dirt

SEB868

Price

/Each

CSA Mass lbs.

max

253

385

253

SEB384

Price

/Each

Price

/Each

CSA Mass lbs.

max.

308

308

308

308

418

min.

122

122

122

122

177

min

133

177

133

- High abrasion resistance
 - Excellent chemical and cut resistance
 - High impact resistance
 - High visibility accents keep you safe in low-light conditions

Lightest and strongest rebar hooks on the market

Thinnest-ever webbing using HI-10[™] Vectran[®] energy

management material for reduced weight and bulk

- Protected labels for durability and longevity
- Rugged and durable soft shock absorber cover is designed to last Certification(s): CSA Standard Z259.11



Model	Mfg.		No. of	Harness	Anchorage	CSA Mass lbs.		Price
No.	No.	Length'	Legs	Connection	Connections	min.	max.	/Each
SEJ418	1246012C	3	One	Snap Hook	Snap Hook	122	308	
SEJ419	1246017C	4	One	Snap Hook	Snap Hook	122	308	
SEJ421	1246102C	6	One	Snap Hook	Rebar Hook	122	308	
SEJ422	1246022C	6	Two	Snap Hook	Snap Hooks	122	308	
SEJ423	1246024C	6	Two	Snap Hook	Rebar Hooks	122	308	

PRO™ Pack Hot Work Shock Absorbing Lanyard

- Lightweight user friendly design
- Fire resistant Kevlar® fiber webbing PVC shock pack with Kevlar® cover
- Energy absorbing design
- limits fall arrest forces
- User friendly self locking
- snap hooks at each end
- Impact indicator
- Harness Connection: Snap Hook
- Certification(s): CSA Standard Z259.11

		Length'	No. of Legs	3	Fall Protection		
Model No.	Mfg. No.			Anchorage Connections	CSA Ma min.	ss lbs. max.	Price /Each
SDP386 SDP388	1340129C 1340186C	6	One Two	Rebar Hook Rebar Hooks	122 122	308 308	
301300	1340100C	4	TWO	NEDAI HUUKS	122	308	

SDP386

SP

PROTECTA

Web Adjustable Positioning Lanyard

No. of

Legs

0ne

One

0ne

Two

Two

- 6 ft. (1.8m) adjustable single-leg lanyard
- Ideal for work positioning or restraint
- Abrasion resistant polyester webbing
- Built-in wear indicator User friendly self locking

Mfg.

13410040

1341001C

1340125C

1340180C

13601800

No.

- snap hooks at each end
- Equipped with i-Safe™
- CSA standard Z259.11, Class B





www.tenaquip.com