

Sealed Blok™ **Self-Retracting Lifelines**

30' Sealed Blok™ self-retracting lifeline that features a retrieval bracket and swivelling snap hook with impact indicator

- New sealed design keeps the critical working components (brake, power spring, energy absorber) free of dirt, grease, water and chemicals
- Built-in carrying handle makes transport and anchoring safe and easy, and provides a secondary "dropped objects protection" attachment point
- Large pivoting anchorage handle stays in line with load for added security and allows use of a variety of connecting hardware
- Anti-ratcheting brake stops falls within inches and limits arresting forces to 900 lbs. for added safety
- Cast aluminum housing and heavy gauge steel end plates resist damage and provide corrosion resistance
- Self-locking swivel hook with impact indicator makes connections easy, and provides a visual means of inspection
- Certified to CSA standard Z259.2.2

Model No. SES589 Mfg. No. 3400850C Price/Each \$







Miller® TurboLite™ & Twin Turbo™ Personal **Fall Limiters**

- First affordable alternative to shock-absorbing lanyards
- Compact and lightweight PFL, workers will no longer need to "switch-out" equipment to maintain a safe fall distance
- Extremely compact and lightweight 1.9 lbs. (0.86 kg)
- Unit attaches directly to the harness back D-ring for greater mobility and versatility
- Engineered webbing for greater abrasion resistance and long service life
- High-strength, impact-resistant nylon housing for maximum durability
- Built-in swivel prevents lifeline from twisting
- Rated for up to a 400 lbs. (181.4 kg) user
- Quick-activating, high-strength
- stainless steel braking system Twin-Turbo™ models feature a G2 connector and 2 legs for 100% tie off
- Certified to CSA standard Z259.2.2



SAR481

MiniLite™ Fall Limiters

- Lightweight, compact design only 2.5 lbs.
- Corrosion-resistant interior, frame and components
- Visual load indicator
- Quick-activating, high-strength stainless steel braking system
- Arrests free falls within inches
- Fits in the palm of your hand
- Provides the best overall value when compared with competitive units
- High-impact protective outer cover
- Prominent reflective labeling
- Available with a variety of integral anchorage connectors
- Snap hook harness connection
- Lenath: 11'
- Certified to CSA standard Z259.2.2

Honeywell MILLER

Model No.	Mfg. No.	Length	Harness ' Connection	Anchorage Connection	Price /Each
TURBO	OLITE™				
SAR481	MFL-1-Z7/6FT	6	Steel Twist-Lock Carabiner	Locking Snap Hook	
SAR482	MFL-3-Z7/6FT	6	None	Locking Snap Hook	
SAR483	MFL-11-Z7/6FT	6	Aluminum Twist-Lock Carabiner	Aluminum Locking Snap Hook	
SEJ629	MFL-12-Z7/6FT	6	Aluminum Twist-Lock Carabiner	Aluminum Locking Rebar Hook	
SEJ633	MFL-1-Z7/9FT	9	Steel Twist-Lock Carabiner	Locking Snap Hook	
SEJ634	MFL-5-Z7/9FT	9	None	Swivel Snap Hook	
SEJ635	MFL-11-Z7/9FT	9	Aluminum Twist-Lock Carabiner	Aluminum Locking Snap Hook	
SEJ636	MFL-12-Z7/9FT	9	Aluminum Twist-Lock Carabiner	Aluminum Locking Rebar Hook	
TWIN '	TURBO™*				
SEJ630	MFLC-3-Z7/6FT	6	G2 Connector	Locking Snap Hooks	
SEJ631	MFLC-4-Z7/6F1	Г 6	G2 Connector	Locking Rebar Hooks	
SEJ632	MFLC-12-Z7/6F	T 6	G2 Connector	Aluminum Locking Rebar Hooks	

* Also available in 9' length

Honeywell **M**ILLER

Model	Mfg.	Anchorage		
No.	No.	Connection		
SG987	FL11-3-Z7/11FT	Twist Lock Carabiner and Swivel Shackle		
SG988	FL11-Z7/11FT	Not Included		
SG989	FL11-1-Z7/11FT	Twist Lock Carabiner		

Miller® Scorpion™ Personal Fall Limiters

- Greater versatility through dual operation:
 - For use as a personal fall limiter or as a traditional retractable lifeline (utilizing a variety of anchorage connectors)
- Small, lightweight design: 2.9 lbs. (1.3 kg)
- Quick-activating, high-strength stainless steel braking system - arrests free falls within inches No annual factory recertification required
- Visual load indicator indicates when
- the unit must be removed from service Variety of integral anchorage
- connectors available 400-lb. (181.4 kg) capacity models
- available upon request Locking snap hook
- harness connection Lenath: 9
- Certified to CSA standard Z259.2.2



SG987

			oneywell <u>M</u> iller	
Model	Mfg.	Anchorage		Price
No.	No.	Connection		/Each
SAK314	PFL-4-Z7/9FT	Carabiner and Swivel Shac	ckle	

Black Rhino™ Self-Retracting Lifelines

- · Repairable; no annual factory recertification required Ideal for concrete construction, welding,
- steel erection and warehouse applications
- Quick-activating, high-strength stainless steel braking system
- Variety of integral anchorage connectors available
- Integral load indicator indicates when the unit must be removed from service
- Extended service life corrosion-resistant stainless steel and aluminum components
- Integral internal shock absorber consistently reduces fall forces to 900 lbs./f (4 kN) or less for greater safety
- Length: 9'
- Certified to CSA standard Z259.2.2



Honeywell <u>M</u>ILLER

Model No.	Mfg. No.	Harness Connection	Anchorage Connection	Price /Each
SAK313	CFL-5-Z7/9FT	Locking Swivel Snap Hook	Locking Swivel Rebar Hook	
SEJ641	CFL-4-Z7/9FT	Locking Swivel Snap Hook	Swivel and Twist Lock Carabiner	