



Cable Ladder Safety Systems

- The Lad-Saf™ flexible cable system consists of a top and bottom bracket that act as anchors for a steel cable that runs the length of the climbing area
- A Lad-Saf™ sleeve connects the worker to the system, automatically follows the user during the climb, and locks on to the cable in the event of a fall
- Designed for ease of use, economy, and versatility
- Integrated tension indicating bottom brackets take the guess work out of installation
- Galvanized and stainless steel construction stands up to harsh environments for added longevity
- Integrated shock absorbing top bracket reduces forces imposed on ladder during a fall
- Intermediate cable guides prevent cable wear against the ladder and permit the climber to bypass without disconnecting
- Complete system includes both top and bottom brackets, cable and cable guides. They do not include a sleeve, carabiner, or harness
- System is also customizable, call today to learn more



Fall Protection

Model No.	Mfg. No.	Length'	Price /Each
SEE810	LADSAF-20	20	
SEE811	LADSAF-30	30	

Lad-Saf™ X2 Detachable Cable Sleeve

- Sleeve for Lad-Saf™ fixed ladder safety system
- For use on 3/8" (9.5 mm) and 5/16" (8 mm) 1 x 7 or 7 x 19 solid core cable
- Mobile design follows user for convenient climbing protection
- Easy to install and detach anywhere along lifeline
- Mechanical and inertial locking system stops falls within inches
- Built-in energy absorber and fall indicator with swivel
- Anti-inversion feature prevents incorrect installation
- Saflok™ steel carabiner for secure connection to harness
- Extremely rugged and corrosion resistant construction
- Extremely compact, lightweight design
- Order top and bottom brackets, cable and guides separately
- Sleeve for Lad-Saf™ fixed ladder safety system
- Attachment: Without Lanyard

Model No. **SDK982**
Mfg. No. 6160030
Price/Each \$



Fall Protection

Rollgliss™ R550 Rescue & Descent Device

- Emergency rescue and evacuation from a wide variety of elevated work areas
- Fully automatic controlled descent
- Bidirectional design enables multiple rescues
- Built-in rescue lifting wheel
- 100 ft. (30.5 m) 3/8" (9.5 mm) kernmantle rope lifeline
- Rated for up to 1 640 ft. (500 m) height for one user, 575 ft. (175 m) for two users
- Compact and lightweight design
- High strength corrosion resistant construction
- Integrated rope ears
- Dual brake design
- Equipped with i-Safe™
- Kit also contains 4 ft. (1.2 m) anchor sling, two carabiners and carrying bag
- No. of users: 2
- Lifeline material: Kernmantle
- Harness connection: Carabiner
- Anchorage connection type: Snap hook
- CSA Standard Z259.2.2

Model No. **SDL610**
Mfg. No. 3327100
Price/Each \$



PULLEY - ROLLGLISS™ R550

- Single
- 9-16 mm

Model No. **SDL611**
Mfg. No. 9504733
Price/Each \$



Fall Protection

Roof Anchors

- Fast and easy installation
- Installs to sloped or flat wood and metal decking roofs
- Non-penetrating design
- Swiveling self-retracting lifeline bracket
- Compact and lightweight design
- Secondary D-ring anchor point
- Adjustable legs, 360-degree swiveling
- Pair the DBI-SALA® roof anchors with the 3M™ DBI-SALA® Smart Lock SRLs



Fall Protection

Model No.	Mfg. No.	Description	Price /Each
SGJ694	2190073	3M™ DBI-SALA® Standing Seam Roof Anchor	
SGJ695	2190071	3M™ DBI-SALA® Swiveling Roof Anchor	
SGJ696	2190074	3M™ DBI-SALA® Construction Roof Anchor	
SGJ697	2190072	3M™ Protecta® Standing Seam Roof Anchor	
SGJ698	2190070	3M™ Protecta® Swiveling Roof Anchor	