



### Comfort Grip Connector

- Transverse load rated self-locking/closing aluminum Comfort Grip connector
- Built-in connector for single-leg SRL direct attachment to harness
- Extremely compact, lightweight design
- Tough and impact-resistant thermoplastic housing
- Swiveling anchorage loop
- Quick-activating speed-sensing brake system
- High-capacity external energy absorber and impact indicator
- i-Safe™ equipped
- Certification: CSA standard Z259.12 for transverse loading
- Note that this connector pairs with many of 3M lanyards and SRLs so multiple configurations are available



Model No. **SGJ693**  
Mfg. No. 1246415  
Price/Each \$



### Concrete Detent Anchors

- Reusable detent pin assembly allows a user to tie-off anywhere a socket is pre-installed with a push of a button
- Lightweight and portable
- Socket can be installed vertically or overhead into a concrete wall, floor, or ceiling
- Rugged, corrosion resistant stainless steel



Model No. **SEJ623**  
Mfg. No. 2101004  
Price/Each \$



### Cable Tie-Off Adaptors

- 1/4" coated galvanized cable
- Lightweight and extremely durable
- Stands up to harsh environments
- Snap hook at one end, O-ring at the other
- Length: 6'



Model No. **SEB470**  
Mfg. No. AJ408CG-6  
Price/Each \$



### Tie-Off Adaptors

- Pass-thru style polyester web tie-off adaptor



Model No.	Mfg. No.	Length'	Price /Each
SEB389	1003000	3	
SEB390	1003006	6	

### D-Ring Anchorage Plates

- Can be bolted or welded to a structure, offering a compact, reliable connection point
- Two 1/2" diameter attachment holes
- Cadmium plated steel D-ring
- 304 stainless steel anchorage plate
- Plate size: 1/4" x 2" x 4 1/2"



Model No. **SEB449**  
Mfg. No. 2101639  
Price/Each \$



### Saflok™ Carabiners

- Steel carabiners
- Self locking/closing
- 3600-lb. gate



SEH168



SEE719



Model No.	Mfg. No.	Gate Opening"	Price /Each
SEH168	2000117	1 1/16	
SEE719	2000113	1 3/16	

### Anchorage Connecting Carabiners

- Zinc plated, 3600-lb. anchorage point
- Easy one-hand operation
- Self-locking
- 3/4" gate opening
- Meets OSHA 1926 and ANSI SZ359 standards



Model No. **SEB926**  
Mfg. No. AJ514A  
Price/Each \$



### Concrete D-Ring Anchors

- Reusable D-ring assembly
- Rugged design for harsh environments
- Safe "hook-up" indicator notifies user of proper installation
- Install into 1 1/16" or 3/4" holes - only standard drill bits needed



Model No. **SEB438**  
Mfg. No. 2104568  
Price/Each \$

