

Fixed Beam Anchors

Installs in seconds to the beam structure in any orientation

Final tightening using a built-in adjustment handle

Model No. SEE808 Mfg. No. 2108406 Price/Each \$







Freestanding Counterweight Anchors

Freestanding system is easily placed on top of the roof surface to provide tie-off point for one worker

Model No. SEE809 Mfg. No. 7200439 Price/Each \$







Lad-Saf™ Rope Grabs

- Mobile design automatically follows users for hands-free operation
- Detachable design can be attached or removed anywhere along lifeline
- Inertia and cam locking systems for safety and to prevent "panic-grab"
- For use on 5/8" (16 mm) polyester/polypropylene rope lifeline

Use with 3' shock absorbing lanyard

Model No. SEB433 Mfg. No. 5000335C Price/Each \$







- 5/8" diameter
- Snap hook at one end
- Features additional abrasion and UV resistance, for added durability, longevity, and safety

Model No. SEC130 Mfg. No. 1202754C Price/Each \$







Cobra™ Mobile/ **Manual Rope Grab** with Lanyard

- Mobile design automatically follows user
- Manual option allows user to fix in place
- Cam locking system for safety
- Integral 2 ft. (0.6 m) Pro™ shock absorbing lanyard
- Detachable anywhere along the lifeline
- Durable and lightweight corrosion-resistant construction
- For use with 5/8" (16 mm) diameter polyester/ polypropylene blend rope lifeline
- Rope Diameter: 5/8"

Model No. SEP896 Mfg. No. AC202C-SA2 Price/Each \$





Sliding Beam Anchor

- Versatile size ranges to fit a variety of beams
- Replaceable wear pads
- 360-degree swiveling D-ring anchor point
- Integrated dual ratcheting system
- High-strength, lightweight steel and aluminum construction
- 5000 lb. strength and up to 420 lb. (189 kg) capacity
- Type: Temporary
- Style: I-Beam

Model No. SGJ699 Mfg. No. 2104710 Price/Each \$







Door/Window Jamb Anchors

- Fits door or window sizes ranging from 21 1/2" to 51 1/2" in width
- Non-penetrating design ensures no damage to structure
- Fast and easy installation with built-in adjustment knob – no tools or drilling are required
- Lightweight and extremely portable design

Model No. SEJ618 Mfg. No. 2100080 Price/Each \$







Beam Trolley Anchorage Connectors

- Installs easily and quickly overhead with no tools necessary at ends or midpoint on beams
- Non-corrosive double-shielded wheel bearings provide smooth and effortless operation
- Trolley guards protect the wheels from damage and keep the beam ahead of the trolley clear of debris
- Provides added maneuverability, improved safety, and increased productivity
- Fits flat or tapered beam flanges 3" to 8" wide, and up to 11/16" thick

Model No. SEJ617 Mfg. No. 2103143 Price/Each \$







Rope Lifelines

- 16 mm (5/8") diameter, polyester sheath with polypropylene core
- Tensile strength: 2540 kg (5600 lbs.)
- · Zinc plated stamped steel hook
- Net weight: 5.6 lbs. (25 kg)







Model	Mfg.		Price
No.	No.	Length'	/Each
SEB381	SSR100-50	50	
SEB382	SSR100-100	100	

