



GX Lifting Clamps

- Entirely drop forged and heat treated
- Strong, yet lightweight
- Ideal for both vertical and horizontal-to-vertical lifting
- Feature a patented wear indicator system
- 100% proof tested



Campbell®

Model No.	Capacity Ton	Grip Range	Wt. lbs.	Price /Each
LB606	1/2	1/16" - 5/8"	4	
LB607	1	1/16" - 3/4"	8	
LB608	3	1/16" - 1"	17	

Universal Lifting Clamps

- Full 180-Degree turning range for material transfer, turning or moving
- Ideal for lifting very hard surface materials
- Welded alloy steel body, forged alloy components
- Individually proof tested to 2 times the WLL with certification
- All lifting clamps are serialized and tagged



Grosby iP®

Model No.	MFG No.	Working Load Limit	Jaw Opening"	Used on Materials w/Surface Hardness	Price /Each
IPU10 SERIES					
LV305	2701675	1000 lbs. (0.5 tons)	0" - 5/8"	363HV10 (345 HB)	
LA232	2701663	2000 lbs (1 ton)	0" - 3/4"	363HV10 (345 HB)	
LV306	2701677	4000 lbs. (2 tons)	0" - 3/4"	363HV10 (345 HB)	
LV307	2701665	6000 lbs (3 tons)	0" - 1-2/5"	363HV10 (345 HB)	
LA546	2701667	9000 lbs (4.5 tons)	0" - 1-3/8"	363HV10 (345 HB)	
LA176	2701669	12 000 lbs. (6 tons)	0" - 2"	363HV10 (345 HB)	

IPU10H SERIES					
LV308	2702175	1000 lbs (0.5 tons)	0" - 5/8"	472HV10 (450 HB)	
LV309	2702177	2000 lbs. (1 ton)	0" - 1-2/5"	472HV10 (450 HB)	
LV310	2702165	4000 lbs. (2 tons)	0" - 1-1/2"	472HV10 (450 HB)	
LV311	2702167	6000 lbs. (3 tons)	0" - 1-1/2"	472HV10 (450 HB)	
LV312	2702169	9000 lbs (4.5 tons)	0" - 2"	472HV10 (450 HB)	
LV313	2702171	12 000 lbs. (6 tons)	0" - 2"	472HV10 (450 HB)	

Vertical Lifting Clamp

- For full vertical lifting, transfer, turning or moving of material
- Welded alloy steel body, forged alloy components
- Individually proof tested to 2 times the WLL with certification
- All lifting clamps are serialized and tagged



Grosby iP®

Model No.	MFG No.	Working Load Limit	Jaw Opening"	Used on Materials w/Surface Hardness	Price /Each
IP10 SERIES					
LV314	2701674	1000 lbs. (0.5 tons)	0" - 5/8"	363HV10 (345 HB)	
LA544	2701662	2000 lbs (1 ton)	0" - 3/4"	363HV10 (345 HB)	
LA545	2701676	4000 lbs. (2 tons)	0" - 3/4"	363HV10 (345 HB)	
LA172	2701664	6000 lbs (3 tons)	0" - 1"	363HV10 (345 HB)	
LV315	2701666	9000 lbs (4.5 tons)	0" - 1-1/2"	363HV10 (345 HB)	
LV316	2701668	12 000 lbs (6 tons)	0" - 2"	363HV10 (345 HB)	

IP10H SERIES					
LV317	2702174	1000 lbs (0.5 tons)	0" - 5/8"	472HV10 (450 HB)	
LV318	2702177	2000 lbs. (1 ton)	0" - 1-2/5"	472HV10 (450 HB)	
LV319	2702164	4000 lbs. (2 tons)	0" - 1-1/2"	472HV10 (450 HB)	
LV320	2702166	6000 lbs. (3 tons)	0" - 1-1/2"	472HV10 (450 HB)	
LV321	2702168	9000 lbs (4.5 tons)	0" - 2"	472HV10 (450 HB)	
LV322	2702171	12 000 lbs. (6 tons)	0" - 2"	472HV10 (450 HB)	

Non-Marring Universal Lifting Clamp

- Full 180-Degree turning range for material transfer, turning or moving
- Welded alloy steel body, forged alloy components
- Individually proof tested to 2 times the WLL with certification
- All lifting clamps are serialized and tagged



Grosby iP®

Model No.	Mfg No.	Working Load Limit	Jaw Opening	Series	Price /Each
LV323	2703811	1000 lbs. (0.5 tons)	0" - 5/8"	IPNM10N	
LV324	2703738	2000 lbs. (1 tons)	0" - 3/4"	IPNM10N	
LV325	2703442	4000 lbs. (2 tons)	0" - 1-1/2"	IPNM10N	

Horizontal Lifting Clamp

- For horizontal lifting of material
- Welded alloy steel body, forged alloy components
- Individually proof tested to 2 times the WLL with certification
- All lifting clamps are serialized and tagged
- Sold/Priced Per: Clamp
- Designed to be used in multiples of 2 clamps according to load, sizing and shape



Grosby iP®

Model No.	Mfg No.	Working Load Limit	Jaw Opening"	Series	Price /Each
LV326	2703297	1000 lbs. (0.5 tons)	0" - 3/4"	IPH10	
LV327	2703298	2000 lbs. (1 tons)	0" - 1-2/5"	IPH10	
LV328	2703522	4000 lbs. (2 tons)	0" - 2-2/5"	IPH10	
LV329	2703523	6000 lbs. (3 tons)	0" - 2-2/5"	IPH10	
LV330	2703524	9000 lbs. (4.5 tons)	0" - 2-2/5"	IPH10	
LV331	2703525	12 000 lbs. (6 tons)	0" - 2-2/5"	IPH10	

Beam Clamp

- Caution: Never exceed work load limit



VANGUARD STEEL LTD.

Model No.	Capacity	Jaw Opening"	Price /Each
LU561	2000 lbs. (1 ton)	0" - 10-1/4"	
LU562	4000 lbs. (2 tons)	0" - 10-1/4"	
LU563	6000 lbs. (3 tons)	0" - 13-15/16"	
LU564	10 000 lbs. (5 tons)	0" - 13-15/16"	
LU565	20 000 lbs. (10 tons)	0" - 14-3/8"	

Beam Clamps

- Lift, transfer and position beams from 3" to 10" flange widths using a rapid adjustment screw spindle
- Widely used as portable quick attachments for hoisting and rigging equipment
- 3" diameter eye has a cross loading capacity of 15° off center



Grosby iP®

Model No.	Cap. Tons	Jaw Opening"	Series	Price /Each
LA178	2	3" - 7 1/2"	IPTK	
LA179	3	3" - 7 1/2"	IPTK	
LA180	4	6" - 10"	IPTK	

Note: Other capacities available