



Nylon Slings

- Used in conjunction with overhead cranes, hoists or winches
- Nylon slings are available in single or double ply to protect heavy, irregular sized loads from scratching or marring
- Slings must be checked frequently
- Should any surface area show signs of wear or cutting, the sling must be replaced immediately
- Each is tagged with manufacturer's name and capacity



DOUBLE EYE SLING TYPE 3

- Commonly used as a basket and/or choker hitch
- For choker hitch pass one eye through the other flat eye, also makes for easy withdrawal from beneath loads



TWISTED EYE SLING TYPE 4

- Reverse eyes make full functional contact with lifting hooks without the use of hardware
- Widely used for both choker and basket hitches



ENDLESS SLING TYPE 5

- Most versatile and widely used sling
- The economical answer to most lifting problems
- Ideal for vertical, choker, and basket hitches

LOAD LIMIT FOR TYPE 3-4 (LBS.)

| Width" | Vertical | | Choker | | Basket | |
|--------|----------|--------|--------|--------|--------|--------|
| | Single | Double | Single | Double | Single | Double |
| 1 | 1600 | 3200 | 1280 | 2400 | 3200 | 6400 |
| 2 | 3100 | 6200 | 2480 | 4960 | 6200 | 12400 |
| 3 | 4700 | 8800 | 3760 | 7040 | 9400 | 17600 |
| 4 | 6200 | 11000 | 4960 | 8800 | 12400 | 22000 |

LOAD LIMIT FOR TYPE 5 (LBS.)

| Width" | Vertical | | Choker | | Basket | |
|--------|----------|--------|--------|--------|--------|--------|
| | Single | Double | Single | Double | Single | Double |
| 1 | 3200 | 6200 | 2560 | 4960 | 6400 | 12400 |
| 2 | 6200 | 12400 | 4960 | 9930 | 12400 | 24800 |
| 3 | 9400 | 17600 | 7520 | 14080 | 18800 | 35200 |
| 4 | 12400 | 22000 | 9920 | 17600 | 24800 | 44000 |

| Type | Width" | Ply | 3' Model No. | Price /Each | 4' Model No. | Price /Each | 6' Model No. | Price /Each | 8' Model No. | Price /Each | 10' Model No. | Price /Each | 12' Model No. | Price /Each |
|--------|--------|--------|--------------|-------------|--------------|-------------|--------------|-------------|--------------|-------------|---------------|-------------|---------------|-------------|
| Type 3 | 1 | Single | LU292 | | LU293 | | LU294 | | LU295 | | LU296 | | LU297 | |
| | | Double | LU316 | | LU317 | | LU318 | | LU319 | | LU320 | | LU321 | |
| | 2 | Single | LU298 | | LU299 | | LU300 | | LU301 | | LU302 | | LU303 | |
| | | Double | LU322 | | LU323 | | LU324 | | LU325 | | LU326 | | LU327 | |
| | 3 | Single | LU304 | | LU305 | | LU306 | | LU307 | | LU308 | | LU309 | |
| | | Double | LU328 | | LU329 | | LU330 | | LU331 | | LU332 | | LU333 | |
| | 4 | Single | LU310 | | LU311 | | LU312 | | LU313 | | LU314 | | LU315 | |
| | | Double | LU334 | | LU335 | | LU336 | | LU337 | | LU338 | | LU339 | |
| Type 4 | 1 | Single | LU340 | | LU341 | | LU342 | | LU343 | | LU344 | | LU345 | |
| | | Double | LU364 | | LU365 | | LU366 | | LU367 | | LU368 | | LU369 | |
| | 2 | Single | LU346 | | LU347 | | LU348 | | LU349 | | LU350 | | LU351 | |
| | | Double | LU370 | | LU371 | | LU372 | | LU373 | | LU374 | | LU375 | |
| | 3 | Single | LU352 | | LU353 | | LU354 | | LU355 | | LU356 | | LU357 | |
| | | Double | LU376 | | LU377 | | LU378 | | LU379 | | LU380 | | LU381 | |
| | 4 | Single | LU358 | | LU359 | | LU360 | | LU361 | | LU362 | | LU363 | |
| | | Double | LU382 | | LU383 | | LU384 | | LU385 | | LU386 | | LU387 | |
| Type 5 | 1 | Single | LU388 | | LU389 | | LU390 | | LU391 | | LU392 | | LU393 | |
| | | Double | LU412 | | LU413 | | LU414 | | LU415 | | LU416 | | LU417 | |
| | 2 | Single | LU394 | | LU395 | | LU396 | | LU397 | | LU398 | | LU399 | |
| | | Double | LU418 | | LU419 | | LU420 | | LU421 | | LU422 | | LU423 | |
| | 3 | Single | LU400 | | LU401 | | LU402 | | LU403 | | LU404 | | LU405 | |
| | | Double | LU424 | | LU425 | | LU426 | | LU427 | | LU428 | | LU429 | |
| | 4 | Single | LU406 | | LU407 | | LU408 | | LU409 | | LU410 | | LU411 | |
| | | Double | LU430 | | LU431 | | LU432 | | LU433 | | LU434 | | LU435 | |

Note: Other sizes, capacities and options available

Polyester Round Slings

- Constructed from multiple high tenacity polyester yarns in an endless/continuous loop
- Excellent resistance to ultra-violet light, rotting and mildew
- The high flexibility allows the sling to conform to the load for a secure hold
- No loss of strength when used in water
- Lightweight, easy to rig, store and clean
- Hook and load contact points can be rotated to extend the service life
- Seamless cover, no edges to wear out
- Maximum temperature exposure: 194°F



| Model No. | Width' | Length' | Colour | Capacity lbs. | | | Price /Each |
|-----------|--------|---------|--------|---------------|--------|------------|-------------|
| | | | | Vertical | Choker | 90° Basket | |
| LT569 | 2 | 4 | Purple | 3000 | 2400 | 6000 | |
| LT570 | 2 | 6 | Purple | 3000 | 2400 | 6000 | |
| LT571 | 2 | 8 | Purple | 3000 | 2400 | 6000 | |
| LT572 | 2 | 4 | Green | 6000 | 4800 | 12000 | |
| LT573 | 2 | 6 | Green | 6000 | 4800 | 12000 | |
| LT574 | 2 | 8 | Green | 6000 | 4800 | 12000 | |
| LT575 | 2 | 6 | Yellow | 9000 | 7200 | 18000 | |
| LT576 | 2 | 8 | Yellow | 9000 | 7200 | 18000 | |

| Model No. | Width' | Length' | Colour | Capacity lbs. | | | Price /Each |
|-----------|--------|---------|--------|---------------|--------|------------|-------------|
| | | | | Vertical | Choker | 90° Basket | |
| LT577 | 2 | 10 | Yellow | 9000 | 7200 | 18000 | |
| LT578 | 3 | 6 | Red | 14000 | 11200 | 28000 | |
| LT579 | 3 | 8 | Red | 14000 | 11200 | 28000 | |
| LT580 | 3 | 10 | Red | 14000 | 11200 | 28000 | |
| LT581 | 4 | 8 | Blue | 23000 | 18400 | 46000 | |
| LT582 | 4 | 10 | Blue | 23000 | 18400 | 46000 | |
| LT583 | 4 | 12 | Blue | 23000 | 18400 | 46000 | |

Note: Other lengths available upon request