



INDUSTRIAL GARBAGE BAGS CHARACTERISTICS

- Excellent strength and puncture resistance eliminates the need for double bagging
- Less harmful for the environment and are certified UL Ecologo by a well recognized Canadian third party certification body
- Material: Recycled Material
- Type: Open Top



| Model No. | Strength | Dim. L" x W" | Qty/Box | Thickness mils |
|--------------|-----------|--------------|---------|----------------|
| BLACK | | | | |
| JM669 | Utility | 22 x 20 | 500 | 0.64 |
| JM670 | Utility | 24 x 22 | 500 | 0.64 |
| JM671 | Utility | 22 x 24 | 500 | 0.64 |
| JM672 | Regular | 36 x 26 | 250 | 0.7 |
| JM673 | Regular | 38 x 30 | 250 | 0.7 |
| JM674 | Regular | 50 x 35 | 200 | 0.75 |
| JM675 | Strong | 36 x 26 | 200 | 0.9 |
| JM676 | Strong | 38 x 30 | 200 | 0.9 |
| JM677 | Strong | 50 x 35 | 125 | 0.9 |
| JM678 | Strong | 48 x 42 | 125 | 0.9 |
| JM679 | X-Strong | 36 x 26 | 125 | 1.2 |
| JM680 | X-Strong | 38 x 30 | 125 | 1.2 |
| JP572 | X-Strong | 50 x 35 | 100 | 1.2 |
| JP573 | X-Strong | 48 x 42 | 75 | 1.2 |
| JO224 | X-Strong | 50 x 50 | 50 | 1.5 |
| JM683 | 2X Strong | 50 x 35 | 75 | 1.9 |
| JO107 | 3X Strong | 38 x 30 | 50 | 3.0 |
| JM684 | 3X Strong | 50 x 35 | 50 | 3.0 |
| WHITE | | | | |
| JM685 | Utility | 22 x 20 | 500 | 0.64 |
| JM686 | Utility | 24 x 22 | 500 | 0.64 |
| CLEAR | | | | |
| JM687 | Utility | 22 x 20 | 500 | 0.64 |
| JM688 | Utility | 24 x 22 | 500 | 0.64 |
| JM689 | Strong | 36 x 26 | 200 | 0.9 |
| JM690 | Strong | 38 x 30 | 200 | 0.9 |
| JM691 | Strong | 50 x 35 | 125 | 0.9 |
| JM692 | Strong | 48 x 42 | 125 | 0.9 |
| JM693 | X-Strong | 36 x 26 | 125 | 1.2 |
| JM694 | X-Strong | 38 x 30 | 125 | 1.2 |
| JP574 | X-Strong | 50 x 35 | 100 | 1.2 |
| JP575 | X-Strong | 48 x 42 | 75 | 1.2 |
| JO156 | 3X Strong | 50 x 35 | 50 | 3.0 |
| JO225 | X-Strong | 50 x 50 | 50 | 1.5 |

